# VXBR100PW-W

Die cast aluminum construction. Wall bracket plus junction box with sturdy mounting lugs. Medium base socket, 1/2" or 3/4" NPS hub size and a variety of globes. incandescent lamp A21 for 100 series, PS25 for 200 Series. Lamp not supplied.

Color: White

Weight: 3.4 lbs

| | |
|---|---|
| **Project:** | **Type:** |
| **Prepared By:** | **Date:** |

### Lamp Info

| | |
|---|---|
| Type | A21 |
| Watts | 75W |
| Shape/Size | N/A |
| Base | N/A |
| ANSI | N/A |
| Hours | N/A |
| Lamp Lumens | N/A |
| Efficacy | N/A |

### Ballast Info

| | |
|---|---|
| Type | N/A |
| 120V | N/A |
| 208V | N/A |
| 240V | N/A |
| 277V | N/A |
| Input Watts | N/A |

## Technical Specifications

### Compliance

**UL Listed:**
Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90°C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases.

### Electrical

**Wattage:**
See catalog number chart for maximumWage with clear glass, colored glass and Permaglobes

**Socket:**
Premium porcelain with 150°C 8" leads attached. Fastened with 2 stainless steel screws.

**Maximum Watts:**
75W

### Construction

**Optional Reflectors:**
Highly reflective white baked polyester epoxy powder finish over a heavy gauge aluminum base. Reflectors thread onto fixtures. See RV series.

**Globe:**
Supplied with white flat bottom prismatic polycarbonate globe. Not for use with diecast or wire guard.

**Optional Guard:**
Order flat bottom guard separately. CAT# GD100BAR.


Copyright © 2025 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

Copyright © 2025 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice