

Twist-Lock® Devices  
30A, 3 Phase 250V AC, 3 Pole, 4 Wire  
Grounding  
Watertight Safety-Shroud® Reverse  
Service Plug

# HUBBELL

## Features

- UL Type 4X Environmental seal protects connection while in use.
- One-piece, engineered thermoplastic housing is impact-resistant for heavy-duty industrial environments
- Superior cord grip design protects terminations from excess strain.

## Ordering Information

Description	Device Color	UPC	Catalog Number
Black PBT housing, white PBT clamps	Black		HBL2723SR

## Listings

Listed to UL 498  
Fed.Spec. W-C-596  
Certified to CSA C22.2 No.42  
UL Listed, CSA Certified to Type 4, 4X and Type 12

## Specifications

Housing	PBT
Contacts	Brass
Terminal Retainer	Clear polycarbonate
Terminal Screws	#10-32 Brass (Phillips / Slotted / Robertson)

## Performance

### Electrical

Current Interrupting Certified for current interrupting at full rated current  
Dielectric Voltage Withstands 2,000V minimum

### Mechanical

Terminal Accommodation #16 AWG - #8 AWG solid or stranded copper wire only.

Terminal Identification Terminals identified in accordance with UL 498

### Environmental

Flammability V0 per UL94 or CSA 22.2 No.0.17  
Moisture Resistance Type 4, 4X, 12, IP66 suitability  
Operating Temperatures Maximum Continuous 75°C Minimum -40°C (w/o impact)



## Accessories

Watertight Safety Shroud	HBL2725SWR
Reverse Service Connector	

## Resources

[eCatalog](#)

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

