



.25x.25x1.75  
KEY

3/4" NPT  
LEAD HOLE

1/4-20UNC-2A  
.38 FULL THD

Ø .41-.46  
THRU-8 HOLES  
(182 FR MAY HAVE  
ONLY 4 HOLES)

NOTES:

1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°
3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FRAME	B	C	BS	2F	MOUNTING
575	182T	5.50	15.18	2.25	4.50	F1 ONLY
675	182T	6.50	16.18	2.75	5.50	F1 ONLY
675	184T	6.50	16.18	2.75	5.50	F1 OR F2

		TOLERANCES UNLESS SPECIFIED				DRAWN TJW 5/19/2009	
		DEC	INCHES			CHK CTO 5/19/2009	
		.X	±.1			APPR EH 5/19/2009	
		.XX	±.03			SCALE 9:32	
		.XXX	±.005			REF SS68446	
		.XXXX	±.0005	MAT'L		FMF CN09-1258	
NO	REVISION	BY & DATE	CHK	ANG	±7'30"	FINISH	PAGE OF
			RFP	5/19/2009	PREV	SIZE	DRAWING NO
			NETWORK FILE NAME		SS69971	<b>A</b>	<b>SS69971</b>
							REV

