

UNITS: INCHES

| FRAME SIZE | MOTOR DIMENSIONS | | | | | | | | | | CONDUIT BOX | | | | | | | | | |
|------------|------------------|-------|------|-------|------|------|-------|-------|-------|------|-----------------|---------|---------|----------|------|-----|----------|------|--|----------------|
| | A | B | C | D | G | J | K | M | O | P | T | AA | AB | AC | AE | AF | XL | XN | | |
| 405TS | 20.3 | 16.5 | 34.1 | 10.00 | 1.2 | 4.0 | 4.1 | 13.4 | 20.3 | 20.3 | 2.8 | 3.00 | 20.2 | 15.1 | 13.0 | 8.7 | 15.7 | 11.5 | | |
| 405T | 20.3 | 16.5 | 37.1 | 10.00 | 1.2 | 4.0 | 4.1 | 13.4 | 20.3 | 20.3 | 2.8 | 3.00 | 20.2 | 15.1 | 13.0 | 8.7 | 15.7 | 11.5 | | |
| FRAME SIZE | MOUNTING | | | | | | | | | | SHAFT EXTENSION | | | KEY SEAT | | | BEARINGS | | | MAXIMUM WEIGHT |
| 405T | E | 2F | H | BA | HA | N-W | V | U | R | S | ES | LS | OS | | | | | | | |
| 405T | 8.00 | 13.75 | 0.81 | 6.62 | 4.25 | 4.00 | 2.125 | 1.845 | 0.500 | 2.75 | 6.313C3 | 6.313C3 | 6.313C3 | 1180 | lbs. | | | | | |
| 405T | 8.00 | 13.75 | 0.81 | 6.62 | 7.25 | 7.00 | 2.875 | 2.450 | 0.750 | 5.62 | 6.317C3 | 6.313C3 | 6.313C3 | 1180 | lbs. | | | | | |

- NOTES:
1. DIMENSION V REPRESENTS LENGTH OF STRAIGHT PART OF SHAFT
 2. MAIN CONDUIT BOX MAY BE ROTATED IN 90° INCREMENTS
 3. KEY DIMENSIONS EQUAL S x S x 5.62 FOR T AND S x S x 2.75 FOR TS (MOTOR SUPPLIED WITH KEY)
 4. MOTOR WEIGHT SHOWN IS MAXIMUM HORSEPOWER IN FRAME
 5. OPPOSITE ROTATION AVAILABLE ONLY BY CONNECTION CHANGE

CUSTOMER: _____ MOTOR MODEL NO.: _____ TAG NO's.: _____

P.O. NO.: _____ HP: _____ VOLTAGE: _____ RPM(SYN.): _____ Hz: _____

FRAME SIZE: _____ PRODUCT TYPE: ODP EQP III, EPACT, & HIGH EFFICIENCY

COMMENTS: _____

PER: _____ DATE: _____

STANDARD (NO AUX. BOXES)

RTD AUX. BOX

SPACE HEATER AUX. BOX

BEARING RTD's

TOSHIBA RESERVES THE RIGHT TO MAKE CHANGES OF TECHNICAL IMPROVEMENT AND THE DATA MAY CHANGE WITHOUT NOTICE PRELIMINARY

DO NOT USE FOR CONSTRUCTION, INSTALLATION, OR APPLICATION PURPOSES UNLESS THE DRAWING IS MARKED AS CERTIFIED CERTIFIED

TOSHIBA OPEN DRIP-PROOF HORIZONTAL FOOT-MOUNTED 3 PHASE INDUCTION MOTOR

TOSHIBA INTERNATIONAL CORPORATION F1 ASSEMBLY

XT SERIES

VISIT OUR WEBSITE AT: www.toshiba.com/ind

TYPICAL MOTOR PERFORMANCE DATA

Model: B1502VLG3USH

| HP | kW | Pole | FL RPM | Frame | Voltage | Hz | Phase | FL Amps |
|-----------|-----|------------|--------|-------|----------------|-------------|----------|---------------|
| 150 | 110 | 2 | 3570 | 405TS | 230/460 | 60 | 3 | 328.00/164.00 |
| Enclosure | IP | Ins. Class | S.F. | Duty | NEMA Nom. Eff. | NEMA Design | kVA Code | Ambient (°C) |
| ODP | 12 | F | 1.15 | CONT | 95.8 | B | G | 40 C |

| Load | HP | kW | Amperes | Efficiency (%) | Power Factor (%) |
|--------------|--------|-------|---------|----------------|------------------|
| Full Load | 150 | 111.9 | 164.0 | 95.9 | 89.0 |
| ¾ Load | 112.50 | 83.9 | 127.2 | 95.9 | 87.8 |
| ½ Load | 75.00 | 55.9 | 90.9 | 95.3 | 83.1 |
| ¼ Load | 37.50 | 28.0 | 59.5 | 89.2 | 66.1 |
| No Load | | | 38.0 | | 6.5 |
| Locked Rotor | | | 1085 | | 29.1 |

| Torque | | | | Rotor wk ² Inertia (lb-ft ²) |
|----------------------|-------------------------|--------------------|-----------------------|---|
| Full Load (lb-ft) | Locked Rotor (% FLT) | Pull Up (% FLT) | Break Down (% FLT) | |
| 221 | 225 | 195 | 340 | 26.50 |

| Safe Stall Time(s) | | Sound Pressure dB(A) @ 1M | Bearings* | | Approx. Motor Weight (lbs) |
|--------------------|-----|------------------------------|-----------|--------|-------------------------------|
| Cold | Hot | | DE | NDE | |
| 32 | 15 | - | 6313C3 | 6313C3 | 1213 |

*Bearings are the only recommended spare part(s).

Motor Options:
Product Family:ODP
Mounting:Footed,Shaft:TS Shaft

| | |
|-------------|--|
| Customer | |
| Customer PO | |
| Sales Order | |
| Project # | |

Tag:

All characteristics are average expected values.

TOSHIBA INTERNATIONAL CORPORATION · HOUSTON, TEXAS U.S.A.


| | | | | | |
|-------------|-----------|------------------|-------------|-------------|---------------|
| Engineering | aacosta | Doc. Written By | D. Suarez | Doc.# / Rev | MPCF-1119 / 0 |
| Engr. Date | 5/15/2012 | Doc. Approved By | M. Campbell | Doc. Issued | 6/8/2011 |

SPEED TORQUE/CURRENT CURVE

Model: B1502VLG3USH

| | | | | | | | | |
|-------------------|---|-------------------|------------------|-------------|----------------|-------------|----------|----------------|
| HP | kW | Pole | FL RPM | Frame | Voltage | Hz | Phase | FL Amps |
| 150 | 110 | 2 | 3570 | 405TS | 230/460 | 60 | 3 | 328.00/164.00 |
| Enclosure | IP | Ins. Class | S.F. | Duty | NEMA Nom. Eff. | NEMA Design | kVA Code | Ambient (°C) |
| ODP | 12 | F | 1.15 | CONT | 95.8 | B | G | 40 C |
| Locked Rotor Amps | Rotor wk ² Inertia (lb-ft ²) | Torque | | | | | | Break Down (%) |
| | | Full Load (lb-ft) | Locked Rotor (%) | Pull Up (%) | | | | |
| 1085 | 26.50 | 221 | 225 | 195 | | | 340 | |

Design Values



| | | | |
|-------------|--|--|-----|
| Customer | | wk ² Load Inertia (lb-ft ²) | - |
| Customer PO | | Load Type | - |
| Sales Order | | Voltage (%) | 100 |
| Project # | | Accel. Time | - |

Tag:

All characteristics are average expected values.

TOSHIBA INTERNATIONAL CORPORATION · HOUSTON, TEXAS U.S.A.

| | | | | | |
|-------------|-----------|------------------|-------------|-------------|---------------|
| Engineering | aacosta | Doc. Written By | D. Suarez | Doc.# / Rev | MPCF-1121 / 0 |
| Engr. Date | 5/15/2012 | Doc. Approved By | M. Campbell | Doc. Issued | 6/8/2011 |

Motor Connection Diagrams
12 Leads

Across-the-Line Starting / Running Connections

Low Voltage Delta



High Voltage Delta



Switch L1 and L2 to reverse rotation

Suitable for Wye-Delta Starting and Limited Part-Winding-Starting.
Please Contact Toshiba International for specific connections.