



Technical information





Main Dimensions & Performance Data

d	5,118 in	Bore diameter
D	11,024 in	Outside diameter
В	3,661 in	Width
C _r	281.025,18 lbf	Basic dynamic load rating, radial
C _{0r}	308.003,597 lbf	Basic static load rating, radial
C _{ur}	26.978,417 lbf	Fatigue load limit, radial
n _G	2.650 1/min	Limiting speed
n _{ər}	1.820 1/min	Reference speed
	60,071 lbs	\${Weight}

Mounting dimensions

d _{a min}	5,787 in	Minimum diameter shaft shoulder
D _{a max}	10,354 in	Maximum diameter of housing shoulder
r _{a max}	0,118 in	Maximum recess radius
Dimensions		
r _{min}	0,157 in	Minimum chamfer dimension
D ₁	9,429 in	Bore diameter outer ring
d ₂	6,386 in	Raceway diameter of the inner ring
d s	0,374 in	Diameter lubrication hole

Temperature range

	_	
T _{min}	-22 °F	Operating temperature min.
T _{max}	392 °F	Operating temperature max.

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product. For further information you can use the contact form on our website.

SCHAEFFLER

Calculation factors

е	0,33	Limiting value of Fa/Fr for the applicability of
		diff. Values of factors X and Y
Υ ₁	2,06	Dynamic axial load factor
Y ₂	3,06	Dynamic axial load factor
Υ ₀	2,01	Static axial load factor

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product. For further information you can use the contact form on our website.