



**FAG****6311-N-C3**

Deep groove ball bearing

Deep groove ball bearing 63...-N, single row,
ring groove, steel sheet metal cage

Technical information



Your current product variant

Type of Seal	Without	Not sealed
Design, bearing outer ring	N	Ring groove for snap ring
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	55 mm	Bore diameter
D	120 mm	Outside diameter
B	29 mm	Width
C _r	83,000 N	Basic dynamic load rating, radial
C _{0r}	47,500 N	Basic static load rating, radial
C _{ur}	3,250 N	Fatigue load limit, radial
n _G	8,500 1/min	Limiting speed
n _{gr}	7,100 1/min	Reference speed
m	1.34 kg	Weight



Mounting dimensions

$d_{a\ min}$	66 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	109 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	2 mm	Minimum chamfer dimension
D_1	101.13 mm	Shoulder diameter outer ring
D_2	104.26 mm	Caliber diameter outer ring
d_1	75.2 mm	Shoulder diameter inner ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	150 °C	Operating temperature max.

Calculation factors

f_0	12.9	Calculation factor
-------	------	--------------------

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed