


FAG


6406-C3

Deep groove ball bearing

Deep groove ball bearing 64, single row, steel sheet metal cage

Technical information





Your current product variant

Type of Seal	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	30 mm	Bore diameter
D	90 mm	Outside diameter
B	23 mm	Width
C_r	45,500 N	Basic dynamic load rating, radial
C_{0r}	25,000 N	Basic static load rating, radial
C_{ur}	1,690 N	Fatigue load limit, radial
n_G	10,800 1/min	Limiting speed
$n_{\vartheta r}$	8,600 1/min	Reference speed
≈m	0.736 kg	Weight

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website: Contact form

Mounting dimensions

$d_{a\ min}$	41 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	79 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	1.5 mm	Maximum fillet radius

Dimensions

r_{min}	1.5 mm	Minimum chamfer dimension
D_1	74.64 mm	Shoulder diameter outer ring
D_2	76.5 mm	Caliber diameter outer ring
d_1	55.55 mm	Shoulder diameter inner ring

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Calculation factors

f_0	13	Calculation factor

Characteristics

- Radial load
- Axial load in one direction
- Axial load in two directions
- Grease Lubrication
- Oil Lubrication
- Not sealed

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website: Contact form