

15.09.2023, 20:52:36 UTC SCHAEFFLER



Technical information





Main Dimensions & Performance Data

d	1,969 in	Bore diameter
D	5,118 in	Outside diameter
В	1,22 in	Width
C _r	21.582,734 lbf	Basic dynamic load rating, radial
C _{0r}	15.512,59 lbf	Basic static load rating, radial
C ur	1.067,896 lbf	Fatigue load limit, radial
n _G	9.200 1/min	Limiting speed
n _{9r}	4.400 1/min	Reference speed
	4,641 lbs	\${Weight}

Mounting dimensions

d _{a min}	2,52 in	Minimum diameter of shaft shoulder
D _{a max}	4,567 in	Maximum diameter of housing shoulder
D _{b max}	4,764 in	Maximum diameter of housing shoulder
r _{a max}	0,083 in	Maximum fillet radius of shaft
r _{a1 max}	0,039 in	Maximum fillet radius of housing

Dimensions

r _{min}	0,083 in	Minimum chamfer dimension
r _{1 min}	0,043 in	Minimum chamfer dimension
D ₁	4,071 in	Shoulder diameter on outer ring wide side face
d ₁	3,437 in	Shoulder diameter on inner ring wide side face
а	2,087 in	Distance between the apexes of the pressure
		cones
α	40 °	Contact angle

Temperature range

T _{min}	-22 °F	Operating temperature min.
T _{max}	302 °F	Operating temperature max.

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product. For further information you can use the contact form on our website.