


Technical information






d	3,15 in	Bore diameter
D	6,693 in	Outside diameter
В	2,283 in	Width
C r	94.424,46 lbf	Basic dynamic load rating, radial
C <sub>0r</sub>	95.548,561 lbf	Basic static load rating, radial
C <sub>ur</sub>	17.760,791 lbf	Fatigue load limit, radial
n <sub>G</sub>	7.200 1/min	Limiting speed
n <sub>ər</sub>	3.450 1/min	Reference speed
	14,33 lbs	\${Weight}

## Mounting dimensions

d <sub>a min</sub>	3,622 in	Minimum diameter shaft shoulder
d <sub>a max</sub>	3,898 in	Maximum diameter of shaft shoulder
D <sub>a max</sub>	6,22 in	Maximum diameter of housing shoulder
d <sub>c min</sub>	4,488 in	Minimum shaft shoulder
r <sub>a max</sub>	0,079 in	Maximum recess radius

## Dimensions

r <sub>min</sub>	0,083 in	Minimum chamfer dimension		
r <sub>1 min</sub>	0,083 in	Minimum chamfer dimension		
S	0,146 in	Axial displacement		
E	5,945 in	Raceway diameter outer ring		
F	3,976 in	Raceway diameter inner ring		
D <sub>1 min</sub>	5,667 in	Minimum rib diameter outer ring		
d <sub>1</sub>	4,346 in	Maximum rib diameter inner ring		
Temperature range				
T <sub>min</sub>	-22 °F	Operating temperature min.		
T <sub>max</sub>	302 °F	Operating temperature max.		



The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product. For further information you can use the contact form on our website.

## Additional information

HJ2316-E

L-washer

