

Bearing		Principal Dimencions			Basic Load Ratings		Speed Ratings		Radius (Mm)	Weight (Kg)	Calculation Factors			
Type	Cage	Bore (Mm) D	Outer (Mm) D	Width (Mm) B	Dynamic (Kn) Cr	Static (Kn) Cor	Grease (Rpm)	Oil (Rpm)	Rsmin	G	E	Y1	Y2	Yo
24036	MB	180	260	100	1030	1900	900	1200	2.1	23.20	0.36	1.88	2.79	1.90
23136	MB	180	300	96	1160	1940	1100	1400	3.0	28.40	0.33	2.05	3.05	2.10
22236	MB	180	320	86	1110	1720	1100	1400	4.0	30.40	0.30	2.25	3.35	2.30
23236	MB	180	320	112	1420	2330	750	1000	4.0	40.80	0.38	1.78	2.64	1.80
22336	MB	180	380	126	1900	2700	850	1100	4.0	68.20	0.38	1.78	2.64	1.80
22336	MA C4 F80	180	380	126	1900	2700	850	1100	4.0	68.20	0.38	1.78	2.64	1.80
22238	CA	190	340	92	1150	1700	1200	1600	4.0	37.30	0.27	2.49	3.71	2.43
22338	CA	190	400	132	1810	2540	880	1200	5.0	82.70	0.35	1.94	2.88	1.89
23038	CA	190	290	75	781	1360	1100	1400	2.1	18.20	0.24	2.76	4.11	2.70
23138	CA	190	320	104	1170	1960	870	1200	3.0	34.90	0.32	2.12	3.15	2.07
23238	CA	190	340	120	1420	2340	760	1000	4.0	48.00	0.33	2.03	3.03	1.99
24038	CA	190	290	100	931	1800	780	1000	2.1	23.80	0.33	2.07	3.09	2.03
24138	CA	190	320	128	1330	2340	650	870	3.0	41.50	0.37	1.82	2.71	1.78
23038	MB	190	290	75	830	1470	1100	1400	2.1	18.60	0.26	2.60	3.87	2.60
24038	MB	190	290	100	1080	1980	850	1100	2.1	24.30	0.34	1.99	2.96	2.00
23138	MB	190	320	104	1320	2290	1100	1400	3.0	35.60	0.34	1.99	2.96	2.00
22238	MB	190	340	92	1220	1870	1000	1300	4.0	37.70	0.30	2.25	3.35	2.30
24138	MB	190	320	128	1540	2750	600	800	3.0	41.80	0.43	1.57	2.34	1.60
23238	MB	190	340	120	1610	2640	750	1000	4.0	48.90	0.38	1.78	2.64	1.80
22338	MB	190	400	132	2060	2920	750	1000	5.0	84.80	0.38	1.78	2.64	1.80
22338	MA C4 F80	190	400	132	1610	2640	750	1000	4.0	48.80	0.36	1.90	2.80	1.80
22240	CA	200	360	98	1290	1910	1100	1500	4.0	43.20	0.27	2.47	3.67	2.41
22340	CA	200	420	138	1990	2800	840	1100	5.0	95.20	0.35	1.95	2.90	1.91
23040	CA	200	310	82	867	1470	1000	1400	2.1	23.30	0.24	2.76	4.11	2.70
23140	CA	200	340	112	1370	2310	830	1100	3.0	43.10	0.32	2.09	3.11	2.04
23240	CA	200	360	128	1580	2620	730	970	4.0	57.80	0.36	1.90	2.83	1.86
24040	CA	200	310	109	1170	2170	730	970	2.1	31.40	0.33	2.03	3.02	1.98
24140	CA	200	340	140	1590	2790	620	830	3.0	53.30	0.40	1.68	2.50	1.64
23940	MB	200	280	60	525	1020	1100	1400	2.1	11.5	0.21	3.14	4.78	3.3
24140	MB	200	340	140	1400	2385	560	750	3.0	51.50	0.43	1.57	2.34	1.60

