



Browning® Stock Minimum Bore Pulleys for "H" Gearbelts are furnished without key-seats or setscrews. They can be bored to size and furnished with keyseats and setscrews at a reasonable extra price.

*Maximum Bores shown will accommodate Standard Keyseats and Setscrew over Keyseat. Slightly Larger Bores are possible with no Ks., Shallow Ks., or S.S. at angle to Ks.

TABLE No. 1 SPECIFICATIONS-STOCK MINIMUM BORE GEARBELT® PULLEYS

PART NUMBER	DIAMETERS			NUMBER OF GROOVES	TYPE	BORE		DIMENSIONS				WT. Lbs.
	PITCH	OUTSIDE	FLANGE			STOCK	MAX.*	F	L	P	H	
FOR H075 AND H100 BELTS, 1/2" PITCH, 3/4" AND 1" WIDE												
14HB100	2.228"	2.174"	2 7/16"	14	2	5/8"	7/8"	1 5/16"	1 7/8"	5/8"	1 5/8"	1.4
16HB100	2.546	2.492	2 7/8"	16	2	5/8"	1 1/8"	1 5/16"	2	3/4"	1 7/8"	2.0
17HB100	2.706	2.652	3	17	2	5/8"	1 1/4"	1 5/16"	2	3/4"	2	2.3
18HB100	2.865	2.811	3 1/8"	18	2	5/8"	1 3/8"	1 5/16"	2	3/4"	2 1/4"	2.8
19HB100	3.024	2.970	3 3/8"	19	2	5/8"	1 1/2"	1 5/16"	2	3/4"	2 3/8"	3.1
20HB100	3.183	3.129	3 3/8"	20	2	5/8"	1 5/8"	1 5/16"	2 1/8"	7/8"	2 1/2"	3.6
21HB100	3.342	3.288	3 5/8"	21	2	3/4"	1 11/16"	1 5/16"	2 1/8"	7/8"	2 5/8"	3.9
22HB100	3.501	3.447	3 13/16"	22	2	3/4"	1 3/4"	1 5/16"	2 1/4"	1	2 3/4"	4.5
24HB100	3.820	3.766	4 1/16"	24	2	3/4"	1 7/8"	1 5/16"	2 1/4"	1	3	5.6
26HB100	4.138	4.084	4 3/8"	26	2	3/4"	2 1/4"	1 5/16"	2 3/8"	1 1/8"	3 3/8"	7.0
28HB100	4.456	4.402	4 11/16"	28	2	3/4"	2 5/16"	1 5/16"	2 3/8"	1 1/8"	3 1/2"	8.0
30HB100	4.775	4.721	5	30	2	3/4"	2 3/8"	1 5/16"	2 3/8"	1 1/8"	3 5/8"	9.1
FOR H150 BELTS, 1/2" PITCH, 1 1/2" WIDE												
14HB150	2.228"	2.174"	2 7/16"	14	2	3/4"	7/8"	1 13/16"	2 3/8"	5/8"	1 5/8"	1.8
16HB150	2.546	2.492	2 7/8"	16	2	3/4"	1 1/8"	1 13/16"	2 1/2"	3/4"	1 7/8"	2.5
17HB150	2.706	2.652	3	17	2	3/4"	1 1/4"	1 13/16"	2 1/2"	3/4"	2	3.0
18HB150	2.865	2.811	3 3/8"	18	2	3/4"	1 3/8"	1 13/16"	2 1/2"	3/4"	2 1/4"	3.4
19HB150	3.024	2.970	3 3/8"	19	2	3/4"	1 1/2"	1 13/16"	2 1/2"	3/4"	2 3/8"	3.9
20HB150	3.183	3.129	3 3/8"	20	2	3/4"	1 5/8"	1 13/16"	2 5/8"	7/8"	2 1/2"	4.5
21HB150	3.342	3.288	3 5/8"	21	2	3/4"	1 11/16"	1 13/16"	2 5/8"	7/8"	2 5/8"	5.0
22HB150	3.501	3.447	3 13/16"	22	2	3/4"	1 3/4"	1 13/16"	2 3/4"	1	2 3/4"	5.8
24HB150	3.820	3.766	4 1/16"	24	2	3/4"	1 7/8"	1 13/16"	2 3/4"	1	3	6.9
26HB150	4.138	4.084	4 3/8"	26	2	3/4"	2 1/4"	1 13/16"	2 3/4"	1	3 3/8"	8.5
28HB150	4.456	4.402	4 11/16"	28	2	3/4"	2 5/16"	1 13/16"	2 7/8"	1 1/8"	3 1/2"	10.1
30HB150	4.775	4.721	5	30	2	3/4"	2 3/8"	1 13/16"	2 7/8"	1 1/8"	3 5/8"	11.5
FOR H200 BELTS, 1/2" PITCH, 2" WIDE												
14HB200	2.228"	2.174"	2 7/16"	14	2	3/4"	7/8"	2 11/16"	2 29/32"	5/8"	1 5/8"	2.3
16HB200	2.546	2.492	2 7/8"	16	2	3/4"	1 1/8"	2 11/16"	3 1/32"	3/4"	1 7/8"	3.3
17HB200	2.706	2.652	3	17	2	3/4"	1 1/4"	2 11/16"	3 1/32"	3/4"	2	3.8
18HB200	2.865	2.811	3 1/8"	18	2	3/4"	1 3/8"	2 11/16"	3 1/32"	3/4"	2 1/4"	4.4
19HB200	3.024	2.970	3 3/8"	19	2	3/4"	1 1/2"	2 11/16"	3 1/32"	3/4"	2 3/8"	5.0
20HB200	3.183	3.129	3 3/8"	20	2	1	1 5/8"	2 11/16"	3 5/32"	7/8"	2 1/2"	5.3
21HB200	3.342	3.288	3 5/8"	21	2	1	1 11/16"	2 11/16"	3 5/32"	7/8"	2 5/8"	5.9
22HB200	3.501	3.447	3 13/16"	22	2	1	1 3/4"	2 11/16"	3 9/32"	1	2 3/4"	6.9
24HB200	3.820	3.766	4 1/16"	24	2	1	1 7/8"	2 11/16"	3 9/32"	1	3	8.3
26HB200	4.138	4.084	4 3/8"	26	2	1	2 1/4"	2 11/16"	3 13/32"	1 1/8"	3 3/8"	10.2
28HB200	4.456	4.402	4 11/16"	28	2	1	2 5/16"	2 11/16"	3 13/32"	1 1/8"	3 1/2"	11.8
30HB200	4.775	4.721	5	30	2	1	2 3/8"	2 11/16"	3 13/32"	1 1/8"	3 5/8"	13.5
FOR H300 BELTS, 1/2" PITCH, 3" WIDE												
16HB300	2.546"	2.492	2 7/8"	16	2	3/4"	1 1/8"	3 3/8"	4 1/16"	3/4"	1 7/8"	4.5
17HB300	2.706	2.652	3	17	2	3/4"	1 1/4"	3 3/8"	4 1/16"	3/4"	2	5.1
18HB300	2.865	2.811	3 1/8"	18	2	3/4"	1 3/8"	3 3/8"	4 1/16"	3/4"	2 1/4"	6.0
19HB300	3.024	2.970	3 3/8"	19	2	3/4"	1 1/2"	3 3/8"	4 1/16"	3/4"	2 3/8"	6.6
20HB300	3.183	3.129	3 3/8"	20	2	3/4"	1 5/8"	3 3/8"	4 3/16"	7/8"	2 1/2"	7.5
21HB300	3.342	3.288	3 5/8"	21	2	3/4"	1 11/16"	3 3/8"	4 3/16"	7/8"	2 5/8"	9.0
22HB300	3.501	3.447	3 13/16"	22	2	1 1/8"	1 3/4"	3 3/8"	4 5/16"	1	2 3/4"	10.9
24HB300	3.820	3.766	4 1/16"	24	2	1 1/8"	1 7/8"	3 3/8"	4 5/16"	1	3	12.0
26HB300	4.138	4.084	4 3/8"	26	2	1 1/8"	2 1/4"	3 3/8"	4 7/16"	1 1/8"	3 3/8"	13.4
28HB300	4.456	4.402	4 11/16"	28	2	1 1/8"	2 5/16"	3 3/8"	4 7/16"	1 1/8"	3 1/2"	15.6
30HB300	4.775	4.721	5	30	2	1 1/8"	2 3/8"	3 3/8"	4 7/16"	1 1/8"	3 5/8"	18.0

D