


Type A



TABLE No. 1 TYPE "A" STEEL PLATE SPROCKETS

PART No.	OUTSIDE DIA.	PITCH DIA	No. TEETH	STOCK BORE	T (NOM.)	WT. LBS.	PART No.	OUTSIDE DIA.	PITCH DIA	No. TEETH	STOCK BORE	T (NOM.)	Wt. Lbs.
41A15	2.65"	2.405"	15	5/8"	.227"	.3	41A32	5.38"	5.101"	32	19/32"	.227"	1.2
41A16	2.80	2.563	16	5/8	.227	.3	41A35	5.86	5.578	35	19/32	.227	1.5
41A17	2.96	2.721	17	5/8	.227	.3	41A36	6.02	5.737	36	19/32	.227	1.5
41A18	3.14	2.879	18	5/8	.227	.3	41A40	6.65	6.373	40	23/32	.227	1.9
41A19	3.30	3.038	19	5/8	.227	.3	41A42	6.97	6.691	42	23/32	.227	2.3
41A20	3.45	3.196	20	5/8	.227	.4	41A45	7.45	7.168	45	23/32	.227	2.6
41A21	3.62	3.355	21	5/8	.227	.4	41A48	7.93	7.645	48	23/32	.227	3.0
41A22	3.75	3.513	22	5/8	.227	.5	41A54	8.89	8.599	54	23/32	.227	3.6
41A23	3.94	3.672	23	5/8	.227	.6	41A60	9.84	9.554	60	23/32	.227	4.5
41A24	4.10	3.831	24	5/8	.227	.6	41A70	11.43	11.145	70	23/32	.227	6.5
41A25	4.26	3.989	25	5/8	.227	.6	41A72	11.75	11.463	72	23/32	.227	6.5
41A26	4.42	4.148	26	5/8	.227	.7	41A80	13.03	12.736	80	23/32	.227	8.4
41A27	4.58	4.307	27	5/8	.227	.8	41A84	13.66	13.372	84	23/32	.227	9.9
41A28	4.70	4.466	28	5/8	.227	.8	41A96	15.57	15.281	96	15/16	.227	11.5
41A30	5.06	4.783	30	19/32	.227	1.1	41A112	18.12	17.828	112	15/16	.227	15.9



Type B



TABLE No. 2 STEEL SINGLE TYPE "B" MINIMUM BORE SPROCKETS

PART No.	DIAMETERS		No. TEETH	TYPE	BORE		DIMENSIONS				Wt. Lbs.
	OUTSIDE	PITCH			STOCK	MAX.*	T NOM.	L MAX.	P	H	
41B6	1.17"	1.000"	6	B	3/8"	3/8"	.227"	7/8"	21/32"	21/32†	.1
41B7	1.34	1.152	7	B	3/8	3/8	.227	7/8	21/32	3/4†	.1
41B8	1.50	1.307	8	B	1/2	1/2	.227	7/8	21/32	63/64	.1
41B9	1.67	1.462	9	B	1/2	5/8	.227	7/8	21/32	1 1/8†	.2
41B10	1.84	1.618	10	B	1/2	3/4	.227	7/8	21/32	1 1/4†	.3
41B11	2.00	1.775	11	B	1/2	7/8	.227	7/8	21/32	1 7/16†	.3
41B12	2.17	1.932	12	B	1/2	15/16	.227	7/8	21/32	1 9/16†	.4
41B13	2.30	2.089	13	B	1/2	1	.227	7/8	21/32	1 9/16†	.5
41B14	2.49	2.247	14	B	1/2	1 1/4	.227	7/8	21/32	1 3/4†	.6
41B15	2.65	2.405	15	B	1/2	1 5/16	.227	7/8	21/32	2 29/32†	.7
41B16	2.80	2.563	16	B	5/8	1 3/8	.227	7/8	21/32	2 1/16	.8
41B17	2.96	2.721	17	B	5/8	1 1/2	.227	1	25/32	2 15/64	.9
41B18	3.14	2.879	18	B	5/8	1 5/8	.227	1	25/32	2 3/8	1.1
41B19	3.30	3.038	19	B	5/8	1 3/4	.227	1	25/32	2 15/32	1.2
41B20	3.45	3.196	20	B	5/8	1 7/8	.227	1	25/32	2 3/4	1.4
41B21	3.62	3.355	21	B	5/8	1 7/8	.227	1	25/32	2 7/8	1.5
41B22	3.75	3.513	22	B	5/8	2	.227	1	25/32	3	1.6
41B23	3.94	3.672	23	B	5/8	2 1/4	.227	1	25/32	3 3/16	1.6
41B24	4.10	3.831	24	B	5/8	2 1/4	.227	1	25/32	3 1/4	1.7
41B25	4.26	3.989	25	B	5/8	2 1/4	.227	1	25/32	3 1/4	1.7
41B26	4.42	4.148	26	B	5/8	2 1/4	.227	1	25/32	3 1/4	1.7
41B27	4.58	4.307	27	B	5/8	2 1/4	.227	1	25/32	3 1/4	1.8
41B28	4.70	4.466	28	B	5/8	2 1/4	.227	1	25/32	3 1/4	1.8
41B30	5.06	4.783	30	B	5/8	2 1/4	.227	1	25/32	3 1/4	2.0
41B32	5.38	5.101	32	B	5/8	2 1/4	.227	1	25/32	3 1/4	2.6
41B35	5.86	5.307	35	B	5/8	2 1/4	.227	1	25/32	3 1/4	2.9
41B36	6.02	5.737	36	B	5/8	2 1/4	.227	1	25/32	3 1/4	2.9
41B40	6.65	6.373	40	B	3/4	2 1/4	.227	1 1/16	27/32	3 1/4	3.3
41B42	6.97	6.691	42	B	3/4	2 3/8	.227	1 1/16	27/32	3 1/2	3.5
41B45	7.45	7.168	45	B	3/4	2 3/8	.227	1 1/16	27/32	3 1/2	3.9
41B48	7.93	7.645	48	B	3/4	2 3/8	.227	1 1/16	27/32	3 1/2	4.3
41B54	8.89	8.599	54	B	3/4	2 3/8	.227	1 1/16	27/32	3 1/2	5.2
41B60	9.84	9.554	60	B	3/4	2 3/8	.227	1 1/16	27/32	3 1/2	6.2
41B70	11.43	11.145	70	B	3/4	2 3/4	.227	1 3/16	31/32	4	7.8
41B72	11.75	11.463	72	B	3/4	2 3/4	.227	1 3/16	31/32	4	8.1
41B80	13.03	12.736	80	B	3/4	2 3/4	.227	1 3/16	31/32	4	9.9
41B84	13.66	13.372	84	B	3/4	2 3/4	.227	1 3/16	31/32	4	10.3
41B96	15.57	15.281	96	B	1	2 3/4	.227	1 3/16	31/32	4	14.1
41B112	18.12	17.828	112	B	1	2 3/4	.227	1 3/16	31/32	4	19.0

*Maximum bore shown is with standard keyway and setscrew over keyway. Slightly larger bores are possible with no keyway. shallow keyway or setscrew at angle to keyway.
†Hub is recessed for chain clearance.
These Type "B" Sprockets are made without keyways and setscrews. They are furnished with minimum bore which can be rebored to size. keywayed and setscrewed for a reasonable extra charge.