



Worm Gear Reducers



Dimensions (Inches) for Style "QH"

C.D.	Basic Unit ★	N.E.M.A. Frame	A	B	C	D	E	F	H	J	K	L	M	N	P	R
1.33	133Q56H	56C	4.00	2.88	3.25	2.00	1.63	1.00	1.72	3.94	4.66	2.12	5.31	2.66	3.05	3.25
1.54	154Q56H	56C	5.13	3.69	4.19	2.75	2.09	1.38	1.91	4.52	5.38	2.75	6.44	3.22	3.45	3.25
1.54	154Q140H	143/145TC	5.13	3.69	4.19	2.75	2.09	1.38	1.91	4.52	5.38	2.75	6.44	3.22	3.45	3.25
1.75	175Q56H	56C	4.81	3.38	4.19	2.75	2.09	1.38	2.06	4.38	5.75	2.75	5.70	2.85	3.81	3.25
1.75	175Q140H	143/145TC	4.81	3.38	4.19	2.75	2.09	1.38	2.06	4.38	5.75	2.75	5.70	2.85	3.81	3.25
2.06	206Q56H	56C	5.50	3.75	5.00	2.88	2.50	1.44	2.28	4.75	6.38	3.00	6.44	3.22	4.34	3.25
2.06	206Q140H	143/145TC	5.50	3.75	5.00	2.88	2.50	1.44	2.28	4.75	6.38	3.00	6.44	3.22	4.34	3.25
2.37	237Q56H	56C	6.13	4.06	5.00	2.88	2.50	1.44	2.50	5.06	6.94	3.56	6.31	3.16	4.88	3.25
2.37	237Q140H	143/145TC	6.13	4.06	5.00	2.88	2.50	1.44	2.50	5.06	6.94	3.56	6.31	3.16	4.88	3.25
2.62	262Q56H	56C	7.12	4.44	6.38	3.38	3.19	1.69	2.94	5.69	8.00	3.69	6.88	3.44	5.57	3.25
2.62	262Q140H	143/145TC	7.12	4.44	6.38	3.38	3.19	1.69	2.94	5.69	8.00	3.69	6.88	3.44	5.57	3.25
2.62	262Q180H	182/184TC	7.12	4.44	6.38	3.38	3.19	1.69	2.94	6.13	8.00	3.69	6.88	3.44	5.57	4.50
3.00	300Q56H	56C	8.50	5.50	7.00	4.00	3.50	2.00	3.25	5.67	8.88	4.50	8.38	4.19	6.25	3.25
3.00	300Q140H	143/145TC	8.50	5.50	7.00	4.00	3.50	2.00	3.25	6.45	8.88	4.50	8.38	4.19	6.25	3.25
3.00	300Q180H	182/184TC	8.50	5.50	7.00	4.00	3.50	2.00	3.25	6.45	8.88	4.50	8.38	4.19	6.25	4.50
3.25	325Q56H	56C	8.50	5.00	7.50	4.00	3.75	2.00	3.50	6.56	9.38	4.50	8.50	4.25	6.75	3.25
3.25	325Q140H	143/145TC	8.50	5.00	7.50	4.00	3.75	2.00	3.50	6.56	9.38	4.50	8.50	4.25	6.75	3.25
3.25	325Q180H	182/184TC	8.50	5.00	7.50	4.00	3.75	2.00	3.50	7.00	9.38	4.50	8.50	4.25	6.75	4.50
3.75	375Q56H	56C	9.50	6.38	8.50	4.75	4.25	2.38	3.88	6.01	10.44	4.93	9.63	4.81	7.63	3.38
3.75	375Q140H	143/145TC	9.50	6.38	8.50	4.75	4.25	2.38	3.88	6.01	10.44	4.93	9.63	4.81	7.63	3.38
3.75	375Q180H	182/184TC	9.50	6.38	8.50	4.75	4.25	2.38	3.88	7.29	10.44	4.93	9.63	4.81	7.63	4.50
3.75	375Q210H	213/215TC	9.50	6.38	8.50	4.75	4.25	2.38	3.88	7.29	10.44	4.93	9.63	4.81	7.63	4.50
4.50	450Q140H	143/145TC	10.88	7.38	9.56	5.81	4.78	2.91	4.50	6.69	11.94	6.42	11.13	5.56	9.00	3.38
4.50	450Q180H	182/184TC	10.88	7.38	9.56	5.81	4.78	2.91	4.50	7.97	11.94	6.42	11.31	5.66	9.00	4.50
4.50	450Q210H	213/215TC	10.88	7.38	9.56	5.81	4.78	2.91	4.50	7.97	11.94	6.42	11.31	5.66	9.00	4.50
5.16	516Q180H	182/184TC	12.50	7.38	11.00	5.81	5.50	2.91	5.31	8.78	13.75	7.42	11.31	5.66	10.47	4.50
5.16	516Q210H	213/215TC	12.50	7.38	11.00	5.81	5.50	2.91	5.31	8.78	13.75	7.42	11.31	5.66	10.47	4.50
6.00	600Q180H	182/184TC	14.50	8.13	12.75	6.38	6.38	3.19	6.50	9.68	16.50	8.25	12.63	6.31	12.50	4.50
6.00	600Q210H	213/215TC	14.50	8.13	12.75	6.38	6.38	3.19	6.50	9.68	16.50	8.25	12.63	6.31	12.50	4.50

Raider Plus

C.D.	N.E.M.A. Frame	T		INPUT		U +.0015	W Keyway -.0000	OUTPUT BORE +								Stock Ratios marked "x"				Wt. Lbs.
		Size	Deep	Bore	Keyway			5	10	15	20	25	30	40	50	60				
1.33	56C	5/16-18	.50	.625	3/16 x 3/32	.6250	3/16 x 3/32	x	x	x	x	x	x	x	x	x	x	x	x	17.0
1.54	56C	5/16-18	.50	.625	3/16 x 3/32	1.0000	1/4 x 1/8	x	x	x	x	x	x	x	x	x	x	x	x	22.0
1.54	143/145TC	5/16-18	.50	.875	3/16 x 3/32	1.0000	1/4 x 1/8	x	x	-	-	-	-	-	-	-	-	-	-	22.0
1.75	56C	5/16-18	.61	.625	3/16 x 3/32	1.0000	1/4 x 1/8	x	x	x	x	x	x	x	x	x	x	x	x	25.0
1.75	143/145TC	5/16-18	.61	.875	3/16 x 3/32	1.0000	1/4 x 1/8	x	x	x	-	-	-	-	-	-	-	-	-	25.0
2.06	56C	3/8-16	.61	.625	3/16 x 3/32	1.4375	3/8 x 1/8	x	x	x	x	x	x	x	x	x	x	x	x	33.0
2.06	143/145TC	3/8-16	.61	.875	3/16 x 3/32	1.4375	3/8 x 1/8	x	x	x	x	x	x	x	x	x	x	x	x	33.0
2.37	56C	3/8-16	.60	.625	3/16 x 3/32	1.4375	3/8 x 1/8	x	x	x	x	x	x	x	x	x	x	x	x	47.0
2.37	143/145TC	3/8-16	.60	.875	3/16 x 3/32	1.4375	3/8 x 1/8	x	x	x	x	x	x	x	x	x	x	x	x	47.0
2.62	56C	3/8-16	.58	.625	3/16 x 3/32	1.9375	1/2 x 1/8	-	x	x	x	x	x	x	x	x	x	x	x	57.0
2.62	143/145TC	3/8-16	.58	.875	3/16 x 3/32	1.9375	1/2 x 1/8	-	x	x	x	x	x	x	x	x	x	x	x	57.0
2.62	182/184TC	3/8-16	.58	1.125	1/4 x 1/8	1.9375	1/2 x 1/8	x	x	-	-	-	-	-	-	-	-	-	-	57.0
3.00	56C	7/16-14	.80	.625	3/16 x 3/32	2.1875	1/2 x 3/16	-	-	x	x	x	x	x	x	x	x	x	x	80.0
3.00	143/145TC	7/16-14	.80	.875	3/16 x 3/32	2.1875	1/2 x 3/16	-	x	x	x	x	x	x	x	x	x	x	x	80.0
3.00	182/184TC	7/16-14	.80	1.125	1/4 x 1/8	2.1875	1/2 x 3/16	-	x	x	x	x	x	x	x	x	x	x	x	80.0
3.25	56C	7/16-14	.80	.625	3/16 x 3/32	2.1875	1/2 x 3/16	-	x	x	x	x	x	x	x	x	x	x	x	83.0
3.25	143/145TC	7/16-14	.80	.875	3/16 x 3/32	2.1875	1/2 x 3/16	-	x	x	x	x	x	x	x	x	x	x	x	83.0
3.25	182/184TC	7/16-14	.80	1.125	1/4 x 1/8	2.1875	1/2 x 3/16	-	x	x	x	x	x	x	x	x	x	x	x	83.0
3.75	56C	1/2-13	1.00	.625	3/16 x 3/32	2.4375	5/8 x 3/16	-	-	-	-	-	-	-	-	x	x	x	x	116.0
3.75	143/145TC	1/2-13	1.00	.875	3/16 x 3/32	2.4375	5/8 x 3/16	-	x	x	x	x	x	x	x	x	x	x	x	116.0
3.75	182/184TC	1/2-13	1.00	1.375	3/16 x 3/32	2.4375	5/8 x 3/16	-	x	x	x	x	x	x	x	x	x	x	x	116.0
3.75	213/215TC	1/2-13	1.00	1.375	5/16 x 3/32	2.4375	5/8 x 3/16	-	x	x	x	x	x	x	x	x	x	x	x	116.0
4.50	143/145TC	5/8-11	1.00	.875	3/16 x 3/32	2.9375	3/4 x 1/4	-	-	-	-	-	-	-	-	x	x	x	x	150.0
4.50	182/184TC	5/8-11	1.00	1.125	1/4 x 1/8	2.9375	3/4 x 1/4	-	-	x	x	x	x	x	x	x	x	x	x	150.0
4.50	213/215TC	5/8-11	1.00	1.375	5/16 x 5/32	2.9375	3/4 x 1/4	-	-	x	x	x	x	x	x	x	x	x	x	150.0
5.16	182/184TC	5/8-11	1.00	1.125	1/4 x 1/8	3.4375	7/8 x 1/4	-	-	-	-	-	-	-	-	x	x	x	x	230.0
5.16	213/215TC	5/8-11	1.00	1.375	5/16 x 5/32	3.4375	7/8 x 1/4	-	x	x	x	x	x	x	x	x	x	x	x	230.0
6.00	182/184TC	5/8-11	1.00	1.375	5/16 x 5/32	3.9375	1 x 1/4	-	-	-	x	x	x	x	x	x	x	x	x	344.0
6.00	213/215TC	5/8-11	1.00	1.375	5/16 x 5/32	3.9375	1 x 1/4	-	-	-	x	x	x	x	x	x	x	x	x	344.0

Dimensions (Inches) for Style "QHT"

Components ♦	G	O	Wt. Lbs.
Ref. No.	Torque Arm Kit		
133QH	133H-TAK	.53	4.16
154QH	154H-TAK	.53	4.55
175QH	175H-TAK	.53	5.06
206QH	206H-TAK	.	