

| Bearing | | ISO dimensions | | | Load ratings | | Speed limits | | Weight | Dimensions | | |
|---------|---------|----------------|-----|-----|--------------|-------|--------------|-----------|--------|------------|-----|----------|
| Type | Version | d mm | D | H | C kN | Co kN | Grease r/min | Oil r/min | kg | D1 | d1 | r1,2 min |
| 51118 | | 90 | 120 | 22 | 65,0 | 200,0 | 1700 | 2600 | 0,65 | 92 | 120 | 1,0 |
| 51218 | | 90 | 135 | 35 | 115,0 | 315,0 | 1200 | 1800 | 1,65 | 93 | 135 | 1,1 |
| 51318 | | 90 | 155 | 50 | 205,0 | 495,0 | 900 | 1400 | 3,69 | 93 | 155 | 1,5 |
| 51120 | | 100 | 135 | 25 | 85,0 | 268,0 | 1600 | 2400 | 0,95 | 102 | 135 | 1,0 |
| 51220 | | 100 | 150 | 38 | 132,0 | 375,0 | 1100 | 1700 | 2,21 | 103 | 150 | 1,1 |
| 51320 | | 100 | 170 | 55 | 235,0 | 595,0 | 800 | 1200 | 4,86 | 103 | 170 | 1,5 |
| 51122 | | 110 | 145 | 25 | 87,0 | 288 | 2500 | 2200 | 1,03 | 112 | 145 | 1,0 |
| 51222 | | 110 | 160 | 38 | 138,0 | 412 | 2000 | 1600 | 2,39 | 113 | 160 | 1,1 |
| 51224 | | 120 | 170 | 39 | 135,0 | 412 | 950 | 1500 | 2,62 | 123 | 170 | 1,1 |
| 51226 | | 130 | 190 | 45 | 188,0 | 575 | 900 | 1400 | 3,93 | 133 | 187 | 1,5 |
| 51226 | M | 130 | 190 | 45 | 212,0 | 620 | 950 | 1400 | 4,44 | 133 | 187 | 1,5 |
| 51128 | M | 140 | 180 | 31 | 107,0 | 377 | 1300 | 1800 | 0,90 | 142 | 178 | 2,0 |
| 51228 | M | 140 | 200 | 46 | 215,0 | 669 | 950 | 1400 | 2,00 | 143 | 197 | 4,5 |
| 51130 | M | 150 | 190 | 31 | 109,0 | 402 | 1200 | 1700 | 1,00 | 152 | 188 | 2,2 |
| 51230 | M | 150 | 215 | 50 | 257,0 | 795 | 900 | 1300 | 5,21 | 153 | 212 | 5,6 |
| 51330 | M | 150 | 250 | 80 | 377,0 | 1200 | 670 | 900 | 9,00 | 154 | 245 | 15,7 |
| 51430 | M | 150 | 300 | 120 | 668,0 | 2242 | - | 650 | 42,00 | 154 | 295 | 4,0 |
| 51132 | M | 160 | 200 | 31 | 112,0 | 427 | 1200 | 1700 | 1,00 | 162 | 198 | 2,3 |
| 51232 | M | 160 | 225 | 51 | 247,0 | 803 | 850 | 1200 | 3,20 | 163 | 222 | 6,5 |
| 51134 | M | 170 | 215 | 34 | 134,0 | 512 | 1100 | 1600 | 1,40 | 172 | 213 | 3,3 |
| 51234 | M | 170 | 240 | 55 | 269,0 | 874 | 800 | 1100 | 4,50 | 173 | 237 | 8,1 |
| 51334 | M | 170 | 280 | 87 | 463,0 | 1570 | 600 | 800 | 13,00 | 174 | 275 | 22,0 |
| 51136 | M | 180 | 225 | 34 | 135,0 | 528 | 1000 | 1500 | 1,50 | 183 | 222 | 3,4 |
| 51236 | M | 180 | 250 | 56 | 294,0 | 986 | 800 | 1100 | 5,00 | 183 | 247 | 8,7 |

