



- NOTES:  
 1. CONDUIT BOX CAN BE ROTATED UP TO 270 ° FROM ITS ORIGINAL POSITION.  
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180 °.  
 3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

1275	284T	26.21	12.50	9.50	---	4.75
1425	284/286T	27.71	13.00	9.50	11.00	5.50
<b>DASH</b>	<b>FRAME</b>	<b>C</b>	<b>B</b>	<b>2F</b>	<b>2FF</b>	<b>BS</b>

		TOLERANCES UNLESS SPECIFIED		marathon electric		DRAWN CAV 10-18-2000
		DEC INCHES				CHK ML 10-18-2000
4	UPDATED TO NEW FRAME DESIGN MU106205	MSG 08-22-2012	MSG	x	±.1	APPR BW 10-18-2000
3	REDRAWN IN AUTOCAD - NO CHANGE	TAT 06-29-2004	ML	xx	±.03	SCALE 1:4
2	ADDED NOTE 3 MU35810	DAH 02-06-2001	ML	xxx	±.005	REF
1	NEW DRAWING MU34031	MSG 08-23-2012	ML	xxxx	±.0005	FMF MU34031
NO	REVISION	BY & DATE	CHK	LANG	±1/2°	PAGE OF
		THIRD ANGLE PROJECTION		FINISH		REV
		RFP 10-18-2000		PREV		SIZE DRAWING NO
		NETWORK FILE NAME SS311057				<b>B</b> <b>SS311057</b>
						REV <b>4</b>