

Male JIC 37° x Male 37° JIC

Features:


- reference SAE 070101
- pressure rating at 70°F (21°C)

Male JIC 37°	Male JIC 37°	PSI	Zinc Plated Steel	
			Part #	Price/E
7/16"-20	7/16"-20	5000	1204-04-04	\$1.20
9/16"-18	9/16"-18	5000	1204-06-06	1.60
3/4"-16	7/16"-20	4500	1204-08-04	3.15
3/4"-16	3/4"-16	4500	1204-08-08	2.35
7/8"-14	3/4"-16	3500	1204-10-08	3.80
7/8"-14	7/8"-14	3500	1204-10-10	4.05
1-1/16"-12	3/4"-16	3500	1204-12-08	5.05
1-1/16"-12	7/8"-14	3500	1204-12-10	4.95
1-1/16"-12	1-1/16"-12	3500	1204-12-12	4.15
1-5/16"-12	1-1/16"-12	3000	1204-16-12	9.05
1-5/16"-12	1-5/16"-12	3000	1204-16-16	7.55
1 5/8"-12	1 5/8"-12	2500	1204-20-20	11.65
1 7/8"-12	1 7/8"-12	2000	1204-24-24	21.30

Male JIC 37° Flare x Male NPTF

Features:

- reference SAE 070102
- pressure rating at 70°F (21°C)



Male JIC 37° Flare	Male NPTF	PSI	Zinc Plated Steel		316 Stainless Steel	
			Part #	Price/E	Part #	Price/E
7/16"-20	1/8"-27	4500	2404-4-2	\$1.20	---	---
7/16"-20	1/4"-18	4500	2404-4-4	1.55	SS2404-4-4	\$15.10
7/16"-20	3/8"-18	4000	2404-4-6	2.05	---	---
7/16"-20	1/2"-18	3000	2404-4-8	4.95	---	---
1/2"-20	1/8"-27	4000	2404-5-2	2.25	---	---
9/16"-18	1/8"-27	4000	2404-6-2	1.75	---	---
9/16"-18	1/4"-18	4000	2404-6-4	1.55	---	---
9/16"-18	3/8"-18	4000	2404-6-6	2.10	SS2404-6-6	22.00
9/16"-18	1/2"-14	3000	2404-6-8	2.45	---	---
3/4"-16	1/4"-18	4000	2404-8-4	2.25	---	---
3/4"-16	3/8"-18	4000	2404-8-6	2.25	---	---
3/4"-16	1/2"-14	3000	2404-8-8	2.55	SS2404-8-8	23.50
3/4"-16	3/4"-14	2500	2404-8-12	4.20	---	---
7/8"-14	1/2"-14	3000	2404-10-8	2.75	---	---
7/8"-14	3/4"-14	2500	2404-10-12	4.05	---	---
1-1/16"-12	1/2"-14	3000	2404-12-8	5.35	---	---
1-1/16"-12	3/4"-14	2500	2404-12-12	4.20	SS2404-12-12	52.00
1-1/16"-12	1"-11 1/2	2000	2404-12-16	6.15	---	---
1-5/16"-12	3/4"-14	2500	2404-16-12	8.80	---	---
1-5/16"-12	1"-11 1/2	2000	2404-16-16	6.25	SS2404-16-16	65.00
1 5/8"-12	1 1/4"-11 1/2	1150	2404-20-20	9.55	---	---
1 7/8"-12	1 1/2"-11 1/2	1000	2404-24-24	16.60	---	---
2 1/2"-12	2"-11 1/2	1000	2404-32-32	42.00	---	---

Male JIC 37° Flare x Female NPTF

Features:

- reference SAE 070103
- pressure rating at 70°F (21°C)



Male JIC 37° Flare	Female NPTF	PSI	Zinc Plated Steel		316 Stainless Steel	
			Part #	Price/E	Part #	Price/E
7/16"-20	1/8"-27	4500	2405-4-2	\$2.40	---	---
7/16"-20	1/4"-18	4500	2405-4-4	2.95	SS2405-4-4	\$19.90
9/16"-18	1/4"-18	4000	2405-6-4	3.05	---	---
9/16"-18	3/8"-18	4000	2405-6-6	3.00	SS2405-6-6	25.50
9/16"-18	1/2"-14	3000	2405-6-8	4.50	---	---
3/4"-16	3/8"-18	4000	2405-8-6	3.80	---	---
3/4"-16	1/2"-14	3000	2405-8-8	4.20	SS2405-8-8	41.00
3/4"-16	3/4"-14	2500	2405-8-12	13.35	---	---
7/8"-14	1/2"-14	3000	2405-10-8	5.95	---	---
1-1/16"-12	3/4"-14	2500	2405-12-12	6.65	SS2405-12-12	67.00
1-1/16"-12	1"-11 1/2	2000	2405-12-16	20.80	---	---
1-5/16"-12	1"-11 1/2	2000	2405-16-16	9.15	SS2405-16-16	112.00
1 5/8"-12	1 1/4"-11 1/2	1150	2405-20-20	19.30	---	---