PRODUCT INFORMATION PACKET



Model No: C4D17VC6A Catalog No: 109079.00

1/3HP.1750RPM.US56C.TENV.90V.CONT.40C.1.0SF.C FACE.DC WASHGUARD ALL-STAINLESS.C4D17VC6A

NEMA



Regal and Leeson are trademarks of Regal Beloit Corporation or one of its affiliated companies.

©2018 Regal Beloit Corporation, All Rights Reserved. MC017097E






Nameplate Specifications


Output HP	0.33 Hp	Output KW	0.25 kW
Voltage	90 V	Current	3.8 A
Speed	1750 rpm	Service Factor	1
Efficiency	74 %	Duty	Continuous
Insulation Class	F	Frame	US56C
Enclosure	Totally Enclosed Non Ventilated	Overload Protector	No
Ambient Temperature	40 °C	Drive End Bearing Size	6205
Opp Drive End Bearing Size	6203	UL	Recognized
CSA	Υ	CE	N

Technical Specifications

Rotation	Reversible	Mounting	Round
Overall Length	11.81 in	Frame Length	7.25 in
Shaft Diameter	0.625 in	Shaft Extension	2.05 in
Outline Drawing	031790-US56C	Connection Diagram	005487

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created: 10/15/2018





EXTERNAL CONNECTIONS FOR CCWLE ROTATION VIEWING LEAD END OF MOTOR WITH RED LEAD POSITIVE AND BLACK LEAD NEGATIVE. FOR CW ROTATION, REVERSE POLARITY.

				UNLES	ERANCES S SPECIFIEI			ELECTRIC MOTORS GEARMOTORS AND DRIVES		TORS	DRAWN	PG 12/10)/04
				DEC.	INCHES		43011				снк		
				.x	±.1					RIVES		PG 12/10,	/04
				.xx	±.01	TITLE	WIRING DIAGRAM PMDC MOTOR			SCALE	5=8		
				.xxx	±.005					REF			
				.xxxx	±.0005	MAT'L.			FMF	109075.0	0		
NO.	REVISION	BY & DATE	СНК	ANG	±1/2*	FINISH			PREV				
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT — DO NOT SCALE THIS PRINT			RFP	•		CAD FILE	005487		SIZE	DRAWING NO			REV.
			DIST				Α	A 005487.01		.01			