


- NOTES:
 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°. (NOT FIELD MODIFIABLE ON PMAC MOTORS)
 3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

6	ADDED " (NOT FIELD MODIFIABLE ON PMAC MOTORS) " TO NOTES MU112617	HV	03-20-2013	MH	DEC	INCHES		DRAWN	PKG 09-03-1996
5	REMOVED .25 NPT FROM REAR BRKT ISAAC 12-2359	DRO	06-05-2012	EH	X	±.1		CHK	ML 09-06-1996
4	ADDED .25 NPT TO REAR BRKT MU108108	SJW	05-16-2012	TB	XX	±.03	TITLE	SCALE 1:4	
3	UPDATED FRAME AND REDRAWN IN SW MU106213	KS	01-26-2012	MJS	XXX	±.005	250TC FR. - BB - TS - C'FACE - TFNA	REF	
2	REVISED .25/.31 TOL WAS .25/.19 MU69891	RJW	01-23-2006		XXXX	±.0005	MAT'L	FMF	
NO	REVISION	BY & DATE	CHK	ANG	±7'30"	FINISH	PREV	PAGE	OF
							NETWORK FILE NAME	SS203152	REV

1050	254TC	24.02	10.25	20.27	4.12	8.25	---
1225	254/256TC	25.77	12.00	22.02	5.00	8.25	10.00
DASH	FRAME	C	B	AG	BS	2F	2FF



SIZE	DRAWING NO	REV
B	SS203152	6