



NOTES:

1. CONNECT LINE LEADS TO L1 AND L2.  
 LOW VOLTAGE: CONNECT AS SHOWN.  
 HIGH VOLTAGE: MOVE LEAD J TO TERM. 3.  
 MOVE LEAD 2 TO TERM. 4.
2. CONNECTIONS ARE SHOWN FOR OPPOSITE STANDARD ROTATION (CW FACING END OPPOSITE SHAFT EXTENSION). INTERCHANGE 5 AND 8 INTERNALLY FOR STANDARD ROTATION.
3. MULTIPLE CAPACITORS ARE CONNECTED IN PARALLEL UNLESS OTHERWISE SPECIFIED.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

|   |                      |                                |  |
|---|----------------------|--------------------------------|--|
| REV. DESC: REMOVE OPTIONAL THERMAL CONNECTION |                      |                                |  |
| REV. LTR: F                                   | VERSION: 01          | TDR: 00000373039               |  |
| ∟03000  | FILE: \AAA\00007\308 | REVISED: 11: 45: 00 08/11/2005 |  |
|   | MTL: -               | BY: ENJOEPO                    |  |

**BALDOR ELECTRIC Co.**

TYPE L, DV, FIX ROT, THERMAL, TERMINAL PLATE (OPP STD)