

# Capstone® 500 Series



- Fits over prescription glasses.
- Lens is coated to prevent fogging.
- Soft vinyl goggle body conforms to facial contours.
- Goggle provides protection against dust and chemical splash.
- Scratch resistant polycarbonate lens provides 99% UVA/B/C protection.
- Removable vent caps allow the user to remove when more ventilation is required or leave in place for unsurpassed chemical splash resistance.

## Gray Goggle with Quick Release Strap

**Part**                      **Lens**  
 GG504T • ● ● ● ●       Clear H2X Anti-Fog

## Chemical Green Goggle with Neoprene Strap

**Part**                      **Lens**  
 GC504TN • ● ●         Clear H2X Anti-Fog

### GENERAL SPECIFICATION

Bridge: 45mm
Lens Base: 5.5 curve
Lens Size Diagonal: 154mm
Lens Size Vertical: 78mm
Lens Thickness: 2.3mm
Overall Length (Lens-Tip): 91mm
Overall Width (Hinge-Hinge): 180mm
PD: 68mm
Weight: 92gm
Strap Length: 540mm
Closest point between temple tips: N/A, strap
Closest point between temple tips: N/A, single lens
Case Weight: 49.76lbs
Case Pack: 144



# Capstone® 500 Series

## PACKAGING

Polybag: 1pc

Bulk in an outer carton: 144 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Single & cylinder lens
Body	PVC	Polyvinyl chloride, flexible fit
	Polycarbonate	Vent parts for air flow
Nose Piece	PVC	Universal integral to frame
Headband	Textile Elastic	Adjustable Elastic

PART	LENS	LENS MARKING	FRAME MARKING
GG504T	 Clear H2X Anti-Fog	P Z87 +	Z87 + D3 / P c SEI CAN/CSA Z94.3-07
GC504TN	 Clear H2X Anti-Fog	P Z87 +	Z87 +

## LENS MARKING

### Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

### UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

### Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

## FRAME MARKING

### Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

D3: Droplet & Splash Test

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices