

GG504T/GC504TN

CAPSTONE® 500 SERIES



PART

GG504T*****

GC504TN*****

LENS

Clear (Anti-Fog)

Clear (Anti-Fog)

- Fits over prescription glasses.
- Cylinder lens is coated to prevent fogging.
- Soft PVC body conforms to facial contours for comfort fit.
- Dual purpose goggle adaptable to many different applications.
- Removable vent caps allow the user to remove when more ventilation is required or leave in place for unsurpassed chemical splash resistance.

GENERAL SPECIFICATION

Bridge: 45mm

Lens Base: 5.5 curve

Lens Size Diagonal: 154mm

Lens Size Vertical: 78mm

Lens Thickness: 2.3mm

Overall Length (Lens-Tip): 91mm

Overall Width (Hinge-Hinge): 180mm

PD: 68mm

Weight: 92gm

Strap Length: 540mm

Closest point between temple tips: N/A, strap

Closest point between temple tips: N/A, single lens

Case Weight: 49.76lbs

Case Pack: 144

GG504T/GC504TN



CAPSTONE® 500 SERIES

PACKAGING

Polybag: 1pc

Bulk in an outer carton: 144 pcs

| COMPONENT | MATERIAL | FEATURES |
|------------|-----------------|----------------------------------|
| Lens | Polycarbonate | Single & cylinder lens |
| Body | PVC | Polyvinyl chloride, flexible fit |
| | Polycarbonate | Vent parts for air flow |
| Nose Piece | PVC | Universal integral to frame |
| Headband | Textile Elastic | Adjustable Elastic |

| PART | LENS | LENS MARKING | FRAME MARKING |
|---------|--|--------------|----------------------------------|
| GG504T |  Clear (Anti-Fog) | P Z87 + | Z87 + / P c SEI CAN/CSA Z94.3-07 |
| GC504TN |  Clear (Anti-Fog) | P Z87 + | Z87 + |

LENS MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices