

FORTRESS®



Black Frame

Part	Lens
SB3710D•	Clear
SB3710DT•	Clear Anti-Fog
SB3715D•	Coffee
SB3720D•	Gray
SB3730D•	Amber
SB3760D•	Infinity Blue
SB3770D•	Silver Mirror
SB3780D•	Indoor/Outdoor Mirror

Silver Frame

Part	Lens
SS3710D•	Clear
SS3720D•	Gray
SS3732D•	Mango
SS3770D•	Silver Mirror
SS3780D•	Indoor/Outdoor Mirror

Gray Frame

Part	Lens
SG3710D•	Clear

- Adjustable nose pad.
- Lightweight sports styling.
- Straight back rubber coated temple tips.
- Vented lens allows air to flow away from the lens.
- Scratch resistant polycarbonate lens provides 99% UVA/B/C protection.

GENERAL SPECIFICATION

Bridge: 16.5mm
Lens Base: 8 Curve
Lens Size Diagonal: 139mm
Lens Size Vertical: 45mm
Lens Thickness: 2.2mm
Overall Length [Lens-Tip]: 120mm
Overall Width [Hinge-Hinge]: 148mm
PD: N/A
Weight: 14.53gm















PACKAGING

Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8.0 base curve, wrap around design with side protection
Frame	Nylon	High style, features rubber temple tip
Nose Piece	Rubber	Soft, comfortable, help hold glasses on the face with very low tension
Temple	Nylon	Flexible, soft and comfortable
Temple Tip	Rubber	
Screw	Polycarbonate	Integral to ratchets

PART	LENS	LENS MARKING	FRAME MARKING
SB3710D	 Clear	P Z87 + U6	P Z87 +
SB3710DT	 Clear Anti-Fog	P Z87 + U6	P Z87 +
SB3715D	 Coffee	P Z87 + U6 L3	P Z87 +
SB3720D	 Gray	P Z87 + U6 L3	P Z87 +
SB3730D	 Amber	P Z87 + U6	P Z87 +
SB3760D	 Infinity Blue	P Z87 + U6 L1.3	P Z87 +
SB3770D	 Silver Mirror	P Z87 + U6 L3	P Z87 +
SB3780D	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 +
SG3710D	 Clear	P Z87 + U6	P Z87 +
SS3710D	 Clear	P Z87 + U6	P Z87 +
SS3720D	 Gray	P Z87 + U6 L3	P Z87 +
SB3732D	 Mango	P Z87 + S	P Z87 +
SS3770D	 Silver Mirror	P Z87 + U6 L3	P Z87 +
SS3780D	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 +

LENS MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact