

Furix®

Wrap-around sunglass style



Black Frame

Part	Lens
SB8510DT••	Clear Anti-Fog
SB8515DT••	Coffee Anti-Fog
SB8520DT••	Gray Anti-Fog
SB8575DT••	Blue Mirror Anti-Fog
SB8580DT•	Indoor/Outdoor Mirror Anti-Fog

White Frame

Part	Lens
SW8520DT•	Gray Anti-Fog
SW8575DT•	Blue Mirror Anti-Fog

- Integrated nose piece.
- Stylish straight back temples.
- Lightweight, contemporary frame.
- Wrap-around sunglass style fits all facial sizes.
- Scratch resistant polycarbonate lens provides 99% UVA/B/C protection.

GENERAL SPECIFICATION

Bridge: 13mm
Lens Base: 8 Curve
Lens Size Diagonal: 66mm
Lens Size Vertical: 38.8mm
Lens Thickness: 2.0mm
Overall Length (Lens-Tip): 145mm
Overall Width (Hinge-Hinge): 133+/-1mm
Weight: 35.6gm
Closest point between lens: 9mm
Closest point between temple tips: 95+/-5mm








PACKAGING

Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base wrap around lens
Frame	Nylon	N/A
Screw	Stainless Steel	Standard Hinge Screw

PART	LENS	LENS MARKING	FRAME MARKING
SB8510DT	 Clear Anti-Fog	P Z87 +	P Z87 +
SB8515DT	 Coffee Anti-Fog	P Z87 + S	P Z87 +
SB8520DT	 Gray Anti-Fog	P Z87 + S	P Z87 +
SB8575DT	 Blue Mirror Anti-Fog	P Z87 + S	P Z87 +
SB8580DT	 Indoor/Outdoor Mirror Anti-Fog	P Z87 + S	P Z87 +
SW8520DT	 Gray Anti-Fog	P Z87 + S	P Z87 +
SW8575DT	 Blue Mirror Anti-Fog	P Z87 + S	P Z87 +

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact