






SURVEYOR®

All Day, Pressure - Free Comfort



Black Frame

Part	Lens
SB6110S•	 Clear
SB6110ST•	 Clear Anti-Fog
SB6120S•	 Gray
SB6145S•	 Ice Orange Mirror
SB6170S•	 Silver Mirror






- Wrap-around, sunglass style fits all facial sizes.
- Cylinder lens demonstrates strength with style and protection.
- Lens provides unrestricted vision, provides protection against 99.9% harmful UV rays.
- Comfort-fit, rubber temples prevent eyewear from slipping to provide maximum performance.

GENERAL SPECIFICATION

Bridge: 24.8mm
Lens Base: 8 curve
Lens Size Diagonal: 67mm
Lens Size Vertical: 41mm
Lens Thickness: 2.1mm
Overall Length (Lens-Tip): 116mm
Overall Width (Hinge-Hinge): 142mm
PD: 72.5mm
Weight: 24g

PACKAGING
Polybag: 1pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base curve, moulded lens attached to the frame
Frame	Polycarbonate	Half Frame
Nose Piece	Rubber	N/A
Sleeve (on temple)	N/A	N/A
Temple	Polycarbonate	N/A
Temple Tips	Rubber	Dual-injection Temple
Hinge Screw	Nickel Silver	Standard Screw

PART	LENS	LENS MARKING	FRAME MARKING
SB6110S	 Clear	P Z87 + U6	P Z87 +
SB6110ST	 Clear Anti-Fog	P Z87 + U6	P Z87 +
SB6120S	 Gray	P Z87 + U6 L3	P Z87 +
SB6145S	 Ice Orange	P Z87 + L3	P Z87 +
SB6170S	 Silver Mirror	P Z87 + L3	P Z87 +

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact