



PYRAMEX
Perform At Your Peak

Venture II® ANSI CE CSA BALLISTIC



RUBBER NOSEPIECE



ADJUSTABLE TEMPLES

Temples adjust to four different lengths

Nosepiece secures the glass and prevents slipping

Passes MIL-PRF 32432 High Velocity Impact Standards



Part No.	Black Frame
SB1810S	Clear
SB1810ST	AF Clear H2X
SB1820S	Gray
SB1820ST	AF Gray H2X
SB1830S	Amber
SB1835S	Sun Block Bronze
SB1840S	Orange
SB1850SF	5.0 IR Filter
SB1860S	Infinity Blue
SB1860SF	3.0 IR Filter
SB1870S	Silver Mirror
SB1875S	Blue Mirror
SB1880S	I/O Mirror
SB1880ST	AF I/O Mirror
SB1890S	Gold Mirror

Part No.	Realtree Hardwoods HD® Frame
SH1810S	Clear
SH1820S	Gray
SH1830S	Amber

Part No.	Metallic Blue Frame
SMB1810S	Clear
SMB1820S	Gray
SMB1880S	I/O Mirror



Part No.	Maroon Frame
SMM1810S	Clear

Part No.	Slate Gray Frame
SSG1810S	Clear

Venture II Readers ANSI CE CSA



RUBBER NOSEPIECE



ADJUSTABLE TEMPLES



Part No.	Black Frame
SB1810R10	Clear +1.0 Mag
SB1810R15	Clear +1.5 Mag
SB1810R15T	AF Clear H2X +1.5 Mag
SB1810R20	Clear +2.0 Mag
SB1810R20T	AF Clear H2X +2.0 Mag
SB1810R25	Clear +2.5 Mag
SB1810R25T	AF Clear H2X +2.5 Mag
SB1810R30	Clear +3.0 Mag

Part No.	Black Frame
SB1820R15	Gray +1.5 Mag
SB1820R20	Gray +2.0 Mag
SB1820R25	Gray +2.5 Mag
SB1820R30	Gray +3.0 Mag
SB1830R15	Amber +1.5 Mag
SB1830R20	Amber +2.0 Mag
SB1830R25	Amber +2.5 Mag
SB1880R15	I/O Mirror +1.5 Mag
SB1880R20	I/O Mirror +2.0 Mag
SB1880R25	I/O Mirror +2.5 Mag

There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●), Canadian (CSA Z94.3) (●) or Ballistic (MIL-PRF-32432) (●) standards.



Venture II®

General Specifications

Weight: 27 gm
 PD: 68 mm
 Bridge: 10.5 mm
 Lens base: 9.75 curve
 Lens size diagonal: 56 mm
 Lens size vertical: 45 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 150 - 163 mm
 Overall width (hinge - hinge): 142 mm

Materials

Lens: polycarbonate (PC)
 Frame: polyhexamethylene adipitimide (nylon 6/6)
 Hinge: polycarbonate (PC) & nylon
 Screw: stainless steel
 Side shields: polycarbonate (PC)
 Nosepiece: polycarbonate (PC) & thermoplastic rubbers (TPR)

Part No.	Lens Markings	Frame Markings
SB1810S	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1810ST	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1820S	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1820ST	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1830S	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1835S	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1840S	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1850SF	P + W 5	P Z87 +
SB1860S	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1860SF	P + W 3	P Z87 +
SB1870S	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1875S	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1880S	P + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1880ST	P + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB1890S	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SH1810S	P + U6	P Z87 +
SH1820S	P + U6 L2.5	P Z87 +
SH1830S	P + U6	P Z87 +
SMB1810S	P + U6	P Z87 +
SMB1820S	P + U6 L2.5	P Z87 +
SMB1880S	P + U6	P Z87 +
SMM1810S	P + U6	P Z87 +
SSG1810S	P + U6	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 W: Welding filter
 S: Special purpose
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light
 L2.5: 29% max visible light

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

Venture II Readers

General Specifications

Weight: 27 gm
 PD: 68 mm
 Bridge: 10.5 mm
 Lens base: 9.75 curve
 Lens size diagonal: 56 mm
 Lens size vertical: 45 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 150 - 163 mm
 Overall width (hinge - hinge): 142 mm

Materials

Lens: polycarbonate (PC)
 Frame: polyhexamethylene adipitimide (nylon 6/6)
 Hinge: polycarbonate (PC) & nylon
 Screw: stainless steel
 Side shields: polycarbonate (PC)
 Nosepiece: polycarbonate (PC) & thermoplastic rubbers (TPR)

Part No.	Lens Markings	Frame Markings
SB1810R10	P + U6	+1.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1810R15	P + U6	+1.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1810R15T	P + U6	+1.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1810R20	P + U6	+2.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1810R20T	P + U6	+2.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1810R25	P + U6	+2.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1810R25T	P + U6	+2.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1810R30	P + U6	+3.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1820R15	P + U6 L2.5	+1.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1820R20	P + U6 L2.5	+2.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1820R25	P + U6 L2.5	+2.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1820R30	P + U6 L2.5	+3.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1830R15	P + U6	+1.50 P Z87 - 2+
SB1830R20	P + U6	+2.00 P Z87 - 2+
SB1830R25	P + U6	+2.50 P Z87 - 2+
SB1880R15	P + U6 L1.7	+1.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1880R20	P + U6 L1.7	+2.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB1880R25	P + U6 L1.7	+2.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 W: Welding filter
 S: Special purpose
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light
 L2.5: 29% max visible light

Frame Marking Symbols

+1.00: magnification of +1.0
 +1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5
 +3.00: magnification of +3.0
 P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 - 2: Rx
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices