

XSG® Kit

Ballistic Eyewear Kit



Black Frame with Temples and Strap

GB4010KIT•••••

Clear Ballistic, Gray Ballistic and Amber Ballistic interchangeable lenses.

All lenses are H2X anti-fog.

- Black ballistic nylon case for storage.
- Interchangeable temples/strap included.
- Design allows air to flow freely reducing heat.
- Flame resistant foam padding forms a seal to keep out dust and airborne particles.
- Strap has Quick Fit retainer for easy on/off.
- Lenses are treated to prevent fogging, scratching, and static, provide 99% protection against harmful UV rays.
- Passes MIL-PRF 32432 High Velocity Impact Standards.

GENERAL SPECIFICATION

Bridge: 13.7mm

Closest Point Between Lens: 18.5mm

Closest Point Between Strap Temple Tips: 56mm

Lens Base: 8.0 Curve

Lens Size Diagonal: 66.3mm

Lens Size Vertical: 44mm

Lens Thickness: 2.3mm

Overall Length (Lens-Tip): 163mm

Overall Width: 136.5mm

Strap Length: 420mm

PD: 68mm




Weight: 28gm

PACKAGING

Box: 1 kit

Case: 60 kits

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8.0 base dual lenses
Outer Frame Sponge	Polycarbonate / EVA	Flexible fitting body with anti-flaming sponge
Inner Frame	Nylon	Flexible fitting body with dual lenses
Parts-1	Polycarbonate	Screwed in frame
Parts-2	Polycarbonate / PVC	Clip on Part - 1
Nose Piece	EVA	Universal, integral to frame
Headband	Polyester	Adjustable textile elastic fixed on clipping parts
Temple Tips	Polycarbonate / PVC	Clip on Parts - 1
Screw	Stainless Steel	Hinge Screw

PART	LENS	LENS MARKING	FRAME MARKING
GB4010KIT	 Clear H2X Anti-Fog	P Z87 + U6	P Z87 +
	 Gray H2X Anti-Fog	P Z87 + U6 L2.5	P Z87 +
	 Amber H2X Anti-Fog	P Z87 + U6	P Z87 +

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact