


5.00 [127] MAX.
SIDE VIEW

TERMINAL BLOCK
SUITABLE FOR
#13 TO #10 AWG
CONDUCTORS
QTY. 1 PER PHASE



Hammond Power Boluffons Inc.

TOLERANCES

MOUNTING CENTERS = +/- .06"

MOUNTING HOLE SIZE = +/- .005"

4.38

[111]

BOTTOM VIEW

THIS DRAWING CONTAINS PROPRIETARY INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS INC., AND IS NOT FOR GENERAL DISTRIBUTION

All Dimensions in Inches mm in Parenthesis

REACTOR



HPS CENTURION R
THREE PHASE DRY TYPE REACTOR
Hammond
Power Solutions CRX0022AC

1.3MH 50/60 HZ 22 AMPS

0.6 KV CLASS TEMP CLASS: 130 TYPE JR-1 TERMINAL TORQUE: 11 LB-IN AMBIENT: 50°C

NOTES:



TITL	E:		3 PHASE LINE REA	CTOR		SHEET _1_	EDB CRX00
				DES:	PBAKER	유	N 3 I
				DATE:	14/06/25	lı ''	22/
NO.	DATE	BY	REVISION	SCALE:	NTS	-	6