## **MASTER** ALTERNATING CURRENT SQUIRREL-CAGE INDUCTION ENCLOSURE: TOTALLY ENCLOSED **MOTORS**

SUBMERSIBLE

140TY THRU 180TY

FRAME

ğ е BD ₽ 2.00 -뛿혀 器 LEAD WIRE LENGTH SEE NOTE (5) WEIGHT 160 8 HOLES

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.

REV. DESC: CHANGE L DIM	DESC: CHANGE L DIM FROM 16.50 TO 16.56 (SH1)		
REV. LTR: A	VERSION: 01	TDR: 000000837009	W.
FILE: \RGG\00016\668	REVISED: 09:10:21 01/30/2014	BY: RGGWT	DIN
MTL: -			

(1) SPECIAL DIMEN (2) "BD" VARIES

DIMENSIONS

모

SIHL LINE.

± .010. +,0000.

 $\Theta$ 

"U" VARIES

-.0005.

9 6

MINIMUM SUBMERGED DEPTH. "AL" VARIES +.004,

-.000.

FACE RUNDUT AND ECCENTRICITY

.008 MAX. T.I.R.

PROTECTIVE CONDUIT FURNISHED BY CUSTOMER.

LEAD WIRE LENGTH

AS SPECIFIED

밓

CERTIFICATION

TAP DEPTH ON 140TY IS .88; 180TY IS 1.38

IM SHT 140TY THRU 180TY

SH 1 of 2