



Cushion Trax® Ultra™ provides the ultimate in high performance anti-fatigue comfort, designed specifically to address the toughest requirements of today's industrial applications. At 3/4" Inch thick, Cushion Trax® Ultra™ is extremely well suited for multi-shift operations in dry work areas.

Test	Test Description	*Results
N/A	Compression Deflection (The greater the deflection, the better the anti-fatigue properties)	@ 20 lbs/sq. in. 0.373 in. @ 40 lbs/sq. in. 0.436 in.
ASTM D-3574 Test H	Rebound (Measured in % rebound)	15%
ASTM D-3884-01	Abrasion Resistance (Measured in weight loss)	@ 500 cycles (-0.3%) @ 1000 cycles (-0.3%)
ASTM C-1028-96	Static Coefficient of Friction	Dry 0.630
ASTM D-2240-02	Durometer / Hardness	Shore A 85
ASTM D-1004-94a-03	Tear Resistance (Measured in lbs.)	54.6
ASTM E648-03	Critical Radiant Flux	0.58 watts/sq. cm
CPSC FF 1-70 (ASTM D2859)	Flammability (Pass/fail)	Pass

*Testing performed by an independent test laboratory.

7/2013



Anti-Fatigue



Anti-Slip



Custom Sizes

- Thickness: 3/4"
- Weight: 2.0 lbs. sq./ft.
- Materials: Vinyl top surface/PVC foam base
- Stock Sizes: 2' x 3', 3' x 5', 3' x 12'
- Roll Sizes: 2' x 75', 3' x 75', 4' x 75'
- Custom sizes in 2', 3', 4' and 5' widths (up to 75')
- NoTrax® exclusive UniFusion™ bond
- Top surface - 100% recycled PVC
- Certified by the NFSI (National Floor Safety Institute)
- RedStop™ non-slip backing technology

