



Justrite Safety Group

## **131 - DANTE™**

PRODUCT INFORMATION BROCHURE





For over 70 years, the name Notrax® has meant superior quality, service, and innovative products. Now this brand is a cornerstone of Justrite Safety Group, offering the widest selection of products to a variety of markets and applications including entrance mats, anti-fatigue/safety mats, and products designed specifically for use in professional food service environments. Notrax® offers a complete selection of floor matting options to meet any application requirement, quality expectation, and budget.

- **Track record of manufacturing high quality mats for over seventy years**
- **All products are manufactured in ISO certified facilities**
- **Notrax® offers anti-fatigue matting, entrance matting, safety matting, food service matting and specialty mats designed for a variety of industries**



**131 - DANTE™** is made with a densely tufted cut-pile Decalon® construction that is a step above the look-alikes and provides much greater moisture retention. 25 ounces of tufted yarn per square yard make it the perfect product for all medium traffic areas including entrances and lobbies. A vinyl non-slip backing helps to minimize mat movement. Dante™ has 33% more carpet than the competitors "best" Olefin mats.

**Material:** Polypropylene Carpet W/Vinyl Backing

## Features and Benefits:

- Drying mat
- Densely tufted cut-pile Decalon® construction - A step above the look-alikes and provides much greater moisture retention
- 25 ounces of tufted yarn per square yard
- Low profile to perform in narrow clearance doorways
- Vinyl backing ensures minimal buckling and mat movement.



MODEL: 131

## SPECIFICATIONS

### APPLICATIONS

- Schools
- Hospital Entrances
- Lobbies
- Entranceways

Stock Sizes	2'x3', 3'x4', 3'x5', 3'x6', 3'x10', 4'x6', 4'x8'
Roll Sizes	3'x60', 4'x60', 6'x60'
Thickness	3/8"
Cut Lengths	3', 4', and 6' widths (up to 60' long)
Colors	<div>Charcoal</div> <div>Brown</div>

## Performance:

	Good	Better	Best	Superior
Wear Retention				
Crush Resistance				
Soil Resistance				
Function & Appearance				



Cut Lengths



Heavy Traffic



# TESTING DATA

Test	Test Description	Results
ASTM D6540	Accelerated Soiling Method	Based on Visual Inspection 4.0 - Vacuum Rating 4.7 - Rating After Extraction
ASTM D412	Breaking Load/Elongation	248.2 lbs/in <sup>2</sup>
ASTM 5252-98a	Accelerated Wear - 4,000 cycles (Hexapod Tumble Drum Tester)	Appearance: 3.3 Color: 3.5
ASTM D3936-05	Delamination	Construction does not allow for Delamination
ASTM D2240-02	Durometer (Hardness)	50
CPSC FF 1-70	Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	Pass

\*Testing performed by an independent test laboratory.

## NOTRAX®

5655 West 73rd Street  
Chicago, IL 60638

**PHONE:** (800) 621-2802

**FAX:** (800) 322-7105

**EMAIL:** saleschicago@checkers-safety.com

[www.notrax.com](http://www.notrax.com)



A PRODUCT OF:



**Justrite**  
Safety Group

Justrite Safety Group is the leading source of safety equipment for flammables and hazardous materials storage and handling, asset protection, environmental protection spill containment, absorbents, specialized chemical storage, cable management, safety showers and eye/face washes, matting, and vehicle safety equipment. Learn more at [Justrite.com](http://Justrite.com), [Checkers-safety.com](http://Checkers-safety.com), and [Notrax.com](http://Notrax.com).