



Justrite Safety Group

## 132 - ESTES®

PRODUCT INFORMATION BROCHURE







For over 70 years, the name Notrax® has meant superior quality, service, and innovative products. Now this brand is a cornerstone of Justrite Safety Group, offering the widest selection of products to a variety of markets and applications including entrance mats, anti-fatigue/safety mats, and products designed specifically for use in professional food service environments. Notrax® offers a complete selection of floor matting options to meet any application requirement, quality expectation, and budget.

- **Track record of manufacturing high quality mats for over seventy years**
- **All products are manufactured in ISO certified facilities**
- **Notrax® offers anti-fatigue matting, entrance matting, safety matting, food service matting and specialty mats designed for a variety of industries**





**132 - ESTES™** features a fashionable high/low looped pile Decalon® yarn that captures debris and dries foot traffic while maintaining its attractive appearance. A dense 25 ounces of tufted yarn per square yard stands up to the toughest environments, and is perfect for any main entranceway or high traffic area. A heavy-weight vinyl non-slip backing ensures minimum movement.

**Material:** Polypropylene Carpet W/Vinyl Backing

## Features and Benefits:

- Drying mat
- Fashionable high/low looped pile Decalon® yarn
- 25 ounces of tufted loop pile yarn per square yard
- Low profile for use in narrow clearance doorways
- Vinyl backing ensures minimal buckling and mat movement
- Recommended product as part of the **GreenTRAX™** program for "Green Cleaning" environments



MODEL: 132

## SPECIFICATIONS

### APPLICATIONS

- Entranceways
- Lobbies
- Schools
- Medium Traffic Areas

Stock Sizes	2'x3', 3'x4', 3'x5', 3'x6', 3'x10', 4'x6', 4'x8'		
Roll Sizes	3'x60', 4'x60', 6'x60'		
Thickness	3/8"		
Cut Lengths	3', 4', and 6' widths (up to 60' long)		
Colors			
	Burgundy	Brown	Navy
			
	Charcoal	Red/Black	Hunter Green

## Performance:

	Good	Better	Best	Superior
Wear Retention	<div><div></div></div>			
Crush Resistance	<div><div></div></div>			
Soil Resistance	<div><div></div></div>			
Function & Appearance	<div><div></div></div>			



# TESTING DATA

Test	Test Description	Results
ASTM D6540	Accelerated Soiling Method	Based on Visual Inspection 4.0 - Vacuum Rating 4.7 - Rating After Extraction
ASTM D412	Breaking Load/Elongation	248.2 lbs/in <sup>2</sup>
ASTM 5252-98a	Accelerated Wear - 4,000 cycles (Hexapod Tumble Drum Tester)	Appearance: 3.3 Color: 3.5
ASTM D3936-05	Delamination	Construction does not allow for Delamination
ASTM D2240-02	Durometer (Hardness)	50
ASTM D1335-05	Tuft Bind of Pile Yarn	14.1 = Superior
CPSC FF 1-70	Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	Pass

\*Testing performed by an independent test laboratory.

## NOTRAX®

5655 West 73rd Street  
Chicago, IL 60638

**PHONE:** (800) 621-2802

**FAX:** (800) 322-7105

**EMAIL:** saleschicago@checkers-safety.com

www.notrax.com



A PRODUCT OF:



Justrite Safety Group is the leading source of safety equipment for flammables and hazardous materials storage and handling, asset protection, environmental protection spill containment, absorbents, specialized chemical storage, cable management, safety showers and eye/face washes, matting, and vehicle safety equipment. Learn more at Justrite.com, Checkers-safety.com, and Notrax.com.