

Push-On Fittings



Dixon™ push-on fittings are intended for use with Lok-On (push-on style) hose only. No hose clamps or ferrules are needed. Push-On fittings will properly grip Lok-On hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.

SAE Thread Size to UNF Thread Size Interchange

SAE Thread number	SAE Tube OD	UNF Thread size	SAE Thread number	SAE Tube OD	UNF Thread size
02	1/8"	5/16" - 24	07	7/16"	11/16" - 24
03	3/16"	3/8" - 24	08	1/2"	3/4" - 16
04	1/4"	7/16" - 20	10	5/8"	7/8" - 14
05	5/16"	1/2" - 20	12	3/4"	1-1/16" - 14
06	3/8"	5/8" - 18			

45° SAE Hose Barb Fittings

male 45° SAE x push-on hose barb



Hose ID	Tube OD	Male UNF	Brass Part #	Price/E	Opt Qty
1/4"	1/4"	7/16"-20	282-0407	\$3.85	100
1/4"	5/16"	1/2"-20	282-0408	3.53	100
3/8"	3/8"	5/8"-18 ¹	282-0610	4.95	50
1/2"	1/2"	3/4"-16	282-0812	6.66	50
5/8"	5/8"	7/8"-14	282-1014	9.56	25
3/4"	3/4"	1-1/16"-14 ¹	282-1217	15.46	25

¹ notch in hex for SAE identification

female 45° SAE swivel x push-on hose barb



Hose ID	Tube OD	Female UNF	Brass Part #	Price/E	Opt Qty
1/4"	3/8"	5/8"-18 ¹	284-0410	\$6.30	50
5/16"	3/8"	5/8"-18 ¹	284-0510	6.44	50
3/8"	3/8"	5/8"-18 ¹	284-0610	5.05	100
3/4"	3/4"	1-1/16"-14 ¹	284-1217	13.00	25

¹ notch in hex for SAE identification

SAE Inverted Flare Fittings

male SAE swivel x push-on hose barb



Hose ID	Tube OD	Male UNF	Brass Part #	Price/E	Opt Qty
1/4"	3/16"	3/8"-24	290-0406	\$8.29	100
1/4"	1/4"	7/16"-24	290-0407¹	5.69	100
1/4"	5/16"	1/2"-20	290-0408	6.68	100
5/16"	5/16"	1/2"-20	290-0508	6.90	50
5/16"	3/8"	5/8"-18	290-0510	8.18	50
3/8"	5/16"	1/2"-20	290-0608	8.00	100
3/8"	3/8"	5/8"-18	290-0610	8.44	50
1/2"	1/2"	3/4"-18	290-0812¹	10.59	50
5/8"	5/8"	7/8"-18	290-1014¹	13.56	25

¹ UNS thread

rigid female SAE x push-on hose barb



Hose ID	Tube OD	Female UNF	Brass Part #	Price/E	Opt Qty
1/4"	3/16"	3/8"-24	292-0406	\$4.20	100
1/4"	1/4"	7/16"-24	292-0407¹	3.82	100
1/4"	5/16"	1/2"-20	292-0408	4.25	100
5/16"	5/16"	1/2"-20	292-0508	4.25	100
3/8"	5/16"	1/2"-20	292-0608	5.76	100
3/8"	3/8"	5/8"-18	292-0610	5.49	50
1/2"	1/2"	3/4"-18	292-0812¹	8.18	25

¹ UNS thread