

# TINGLEY

est. 1896

## Safetyflex® Overall

**Stock Number - O41008**



**Compliance Standards:** Flame resistant. Self extinguishing with flameout and afterglow less than or equal to 2 seconds after removal of ignition source and char length of less than 6 inches. Test Method ASTM D6413.

**Garment Detail:**

2-Piece bib overall has a plain front, take-up snaps on each leg cuff, white elastic suspenders, a plastic suspender divider and snap-lock buckles.

**Garment Type:** High performance rainwear, provides superior protection against acids, caustics, and chemicals.

**Sizes:** S, M, L, XL, 2X, 3X, 4X

**Color:** Green

**Material:** Green material is 13 oz./yd<sup>2</sup> Specialty PVC on 150D Polyester.

**Seam Construction:** All seams are RF/heat sealed and 100% waterproof.

**Labels/Tags:**

Label sealed to inside center back of waist hem that displays Tingley logo, size, Flame Resistance and country of origin. Care instructions, fabric composition, lot and date codes are located on the reverse.

**Closure Type:**

**Packaging:** Printed polyethylene bag.

**Pockets:**

**Other:** Mildew Resistant.

Dimensions	S	M	L	XL	2X	3X	4X	5X	6X
Waist	42.5"	46"	50"	54"	58"	62"	66"	70"	74"
Inseam	28"	29"	30"	31"	32"	32"	32"	33"	33.5"

**Case Pack:** 12 each

**Case Dimensions/Weight**

S = 15"(L) X 13"(W) X 9"(H) / 19 lbs.

3X = 15"(L) X 13"(W) X 9"(H) / 26 lbs.

M = 15"(L) X 13"(W) X 9"(H) / 20 lbs.

4X = 15"(L) X 13"(W) X 9"(H) / 29 lbs.

L = 15"(L) X 13"(W) X 9"(H) / 21 lbs.

5X = 15"(L) X 13"(W) X 9"(H) / 31 lbs.

XL = 15"(L) X 13"(W) X 9"(H) / 22 lbs.

6X = 15"(L) X 13"(W) X 9"(H) / 33 lbs.

2X = 15"(L) X 13"(W) X 9"(H) / 24 lbs.

Safetyflex® is a registered trademark of Tingley Rubber Corp.