

TINGLEY

est. 1896

DuraBlast™ Jacket

Stock Number - J56147



Compliance Standards: Flame resistant. Self extinguishing with flameout and afterglow less than or equal to 2 seconds after removal of ignition source and char length of less than 6 inches. Test Method ASTM D6413.

Garment Detail:

The jacket has raglan sleeve construction with 90 degree sleeve-to-body angle, a fly front with snap and 'hook and loop' closure, a storm flap, and FR Logo on the left breast. The jacket has 'hook and loop' take-up strap located at each sleeve cuff, an attached hood, snap located at each sleeve cuff, an attached located at each sleeve cuff, an attached hood, and a drawcord at the sweep.

Garment Type: Designed to meet the protection and safety needs of customers who require durable self-extinguishing rainwear.

Sizes: S, M, L, XL, 2X, 3X, 4X, 5X

Color: Yellow

Material: Yellow material is 8 oz./yd² PVC on Polyester scrim.

Seam Construction: All seams are RF/heat sealed and 100% waterproof.

Closure Type: Snap closure with 4 snaps, 'hook and loop' closures at each sleeve cuff and throat guard and storm fly.

Pockets:

Labels/Tags:

Label sealed to inside collar displays Tingley logo, size, Flame Resistance and country of origin. Care instructions, fabric composition, lot and date codes are located on the reverse.

Packaging: Printed polyethylene bag.

Other: Mildew Resistant.

Dimensions	S	M	L	XL	2X	3X	4X	5X
Chest	45"	49"	53"	57"	61"	65"	69"	73"
Length	29"	30"	31"	31"	32"	32"	32"	33"
Sleeve Length	33.5"	34"	35"	35.5"	36"	36.5"	37"	37.5"

Case Pack: 12 each

Case Dimensions/Weight

S = 15"(L) X 13"(W) X 9"(H) / 24 lbs. 2X = 15"(L) X 13"(W) X 9"(H) / 26 lbs.

M = 15"(L) X 13"(W) X 9"(H) / 25 lbs. 3X = 15"(L) X 13"(W) X 9"(H) / 27 lbs.

L = 15"(L) X 13"(W) X 9"(H) / 25 lbs. 4X = 15"(L) X 13"(W) X 9"(H) / 28 lbs.

XL = 15"(L) X 13"(W) X 9"(H) / 26 lbs. 5X = 15"(L) X 13"(W) X 9"(H) / 29 lbs.

DuraBlast™ is a trademark of Tingley Rubber Corp.