


U-Series Universal Pneumatic Couplings

Features:

- temperature range: **-40°F to 250°F (-40°C to 112°C)**
- 2U-Series 6-in-1 (Aro 210, Industrial, Truflate, Lincoln, Italian, and CEJN 320)
- 3U-Series 4-in-1 (ARO 310, Industrial, Truflate, and CEJN 410)
- Parker UC-Series, Hansen Auto-Flo 23, and Tomco Series UC
- Each coupler only accepts three pneumatic nipple styles. Although the universal coupler permits multiple series nipples to mate with one coupler, it is recommended to match like series couplers and nipples. When using a Universal coupler, the lower performance rating between the coupler and nipple must take precedence.
- Some pneumatic applications require the pressurized air to be 'dried' to ensure proper operation of equipment and/or application of product (ie. auto body shops). It is best to match like series couplers and nipples in these applications. If it is necessary to use a Universal coupler, lube the seal and valve area regularly to ensure reliable service.
- for air service only 

Female Couplers

Body Size	Threads	Brass	
		Part #	Price/E
1/4"	1/4" - 18 NPT	2UF2-B	\$18.11
	3/8" - 18 NPT	2UF3-B	18.76
3/8"	3/8" - 18 NPT	3UF3-B	35.25



Male Couplers

Body Size	Threads	Brass	
		Part #	Price/E
1/4"	1/4" - 18 NPT	2UM2-B	\$18.11
	3/8" - 18 NPT	2UM3-B	19.84
3/8"	3/8" - 18 NPT	3UM3-B	35.25



Standard Hose Barb Couplers

Body Size	Hose ID	Brass	
		Part #	Price/E
1/4"	1/4"	2US2-B	\$19.23
	3/8"	2US3-B	19.84
3/8"	3/8"	3US3-B	35.55



Push-On Hose Barb Couplers

Body Size	Hose ID	Brass	
		Part #	Price/E
1/4"	1/4"	2UB2-B	\$20.02
	3/8"	2UB3-B	20.02

