Scheduling Devices Count Down Wall Switch Timers

Features

- 12 hour timer
- · Pre-set 5 button selection with permanent time markings
- · Manual override to OFF
- Alert to OFF function red LED will flash during the final 30 seconds
- Designed for use on 120 or 277V AC circuits







Ordering Information

Description Count down timer wall switch; settings: OFF, 2, 4, 8, 12 hours UPC Number 783585256450

50 Catalog Number 50 DT5012LA

Listings

cULus listed to UL60730-1 and UL60730-2 Meets ASHRAE 90.1, and CEC Title 24 compliant

Specifications

Housing Mounting Bracket Wire Leads Mounting Strap Polycarbonate Aluminum 6" 14AWG copper wire Steel

Performance

Controls 5 button selection LED Indicators OFF Switch

Environmental

Operating Temperature

Electrical Load Capacity

Storage

Preset time selection Illuminates once time is selected 6 seconds to 20 minutes (default set to 10 minutes)

120VAC, 600W Incandescent, 5A Ballast, 5A CFL/LED, 277V; Horsepower rating 1/6

32°F to 122°F (0°C to 50°C) with rate of change not exceeding 20°F(11°C) per hour -40°F to 150°F (-40°C to 65°C); 20% to 90% non condensing relative humidity

Complementary Products

Nylon Wallplate	NP26LA
SS Wallplate	SS26
Snap-On Wallplate	NPS26LA

Online Resources

Customer Use Drawing eCatalog Installation Instructions



Wiring Device-Kellems

