Watertight Devices Accessories Portable Outlet Box

HUBBELL

Features

- Fully thermoplastic elastomer housing exceeds UL crush requirements
- Wiring room large enough to accommodate the broadest range of device requirements
- Brass inserts for maximum strength

Ordering Information

Description	Device Color	UPC	Catalog Number
Portable outlet box;	Black	783585433837	HBL3080BK
deep; no strain relief			

Listings

Listed to UL514C UL Type 3R Meets NEMA WD-1, WD-6 and ANSI standards

Specifications

Box Enclosure	Thermoplastic Elastomer	
Gotcha Ring	Polypropylene	
Locknut	Steel, Zinc Plate	
Threaded Inserts	Brass	


Performance

Environmental

Flammability UL94 V-0
Moisture Resistance UL Type 3R

Operating temperatures -40°C (without impact) to +60°C continuous UV Resistance All exposed materials are UV stabilized





Complementary Products

Gray connector, 0.38"-0.50"	SHC1039CR
Gray connector, 0.50"-0.63"	SHC1040CR
Gray connector, 0.63"-0.75"	SHC1041CR
Gray connector, 0.75"-0.88"	SHC1042CR
UL Type 1 duplex outlet box cover	HBL3051
UL Type 3R duplex outlet box cover	HBL3056
UL Type 1 outlet box cover with 1.39" diameter single receptcale	HBL3052
UL Type 3R outlet box cover with 1.39" diameter single receptacle	HBL3057
UL Type 1 outlet box cover with 1.57" diameter single receptacle	HBL3055
UL Type 3R outlet box cover with 1.57" diameter single receptacle	HBL3058
UL Type 1 outlet box cover for GFCI receptacle	HBL3060
UL Type 3 outlet box cover for GFCI receptacle	HBL3061
Blank outlet box coverplate	HBL3054

Online Resources

eCatalog

