

HUBBELL Circuit-Lock® Non-Metallic Disconnects Now Labelless

- Same Catalog Number
- New Permanent Markings
- Same Great Features

Hubbell's Circuit-Lock® non-metallic disconnects are frequently used in harsh environments. Frequent wash down, hot and high pressure water, caustic cleaning agents and UV light are common place. Hubbell's new laser marked covers ensure that ratings are now permanently marked.

FEATURES

- Permanent Labelless Marking
- IP69k and Type 4X,12 Water Ingress Protection
- Certified by NSF for hygiene in Food Processing applications
- Molded in corrosion and impact resistant material that is UV stabilized
- SCCR rating of 65kA when protected by Class J fuses
- Highly visible red handle which meets OSHA LO/TO capabilities
- Cover cannot be removed with switch in the "On" position
- Accepts Up to 2 Auxiliary Contacts
- Available in Variable Frequency Drive (VFD) and MotorQuick Versions



Same Great
Hubbell Device
Without the Label



Non-Metallic Disconnects Joins the Family of Labelless Disconnects



Non-Metallic



Square Top
Stainless Steel



Sloped Top
Stainless Steel

Available in:
30 Amp
60 Amp
100 Amp
VFD
Motor-Quick®



Rating Information



Water & Dust Ingress Protection:

IP69k Water Test

Extremely Hot (176°) and High Pressure Water (1450 psi) sprayed from various angles.

IP69k Dust Test

Device is placed in a dust chamber for 8 hours while a vacuum tries to pull dust into the sealed device.



National Sanitation Foundation (NSF)

Known as The Most Trusted Name in Food Safety™, NSF International has been helping businesses in the agriculture, processing, food equipment, restaurant and retail industries to navigate the food safety and regulatory environment for nearly 70 years.

© 2014 NSF International. All rights reserved.

Ordering Information



Labelless 30, 60 and 100 Amp Unfused Disconnect Switches

Description	Non-Metallic	Stainless Steel Square Top	Stainless Steel Sloped Top
30A disconnect switch	HBLDS3	HBLDS3SS	HBLDS3SSR
30A disconnect switch with HBLAC1 auxiliary contact	HBLDS3AC	HBLDS3SSAC	HBLDS3SSRAC
30A disconnect switch for use with variable frequency drives	HBLDS3VFD	HBLDS3SSVFD	HBLDS3SSRVFD
60A disconnect switch	HBLDS6	HBLDS6SS	HBLDS6SSR
60A disconnect switch with HBLAC1 auxiliary contact	HBLDS6AC	HBLDS6SSAC	HBLDS6SSRAC
60A disconnect switch for use with variable frequency drives	HBLDS6VFD	HBLDS6SSVFD	HBLDS6SSRVFD
100A disconnect switch	HBLDS10	HBLDS10SS	HBLDS10SSR
100A disconnect switch with HBLAC1 auxiliary contact	HBLDS10AC	HBLDS10SSAC	HBLDS10SSRAC
100A disconnect switch for use with variable frequency drives	HBLDS10VFD	HBLDS10SSVFD	HBLDS10SSRVFD

30A MotorQuick® Unfused Disconnect Switches
UL Type 4X, 12 and IP69k



Description	Non-Metallic	Stainless Steel Square Top	Stainless Steel Sloped Top
Disconnect switch with one pre-wired LINKOSITY® female receptacle (load side)	HBLDS3MQR	HBLDS3SSMQR	HBLDS3SSRMQR
Disconnect switch with 5 foot pre-wired LINKOSITY® female cable (load side)	HBLDS3MQ5	HBLDS3SSMQ5	HBLDS3SSRMQ5
Disconnect switch with one pre-wired LINKOSITY® male receptacle (line side) and one pre-wired LINKOSITY® female receptacle (load side)	HBLDS3MQR2	HBLDS3SSMQR2	HBLDS3SSRMQR2

Labelless Replacement Covers

Description	Non-Metallic*	Stainless Steel Square Top	Stainless Steel Sloped Top
For 30A switches	HBLDS3RC	HBLDS3SSRC	HBLDS3SSRRC
For 60A switches	HBLDS6RC	HBLDS6SSRC	HBLDS6SSRRC
For 100A switches	HBLDS10RC	HBLDS10SSRC	HBLDS10SSRRC

*Laser Marked