

## Dixon Type C Couplers

female coupler x hose shank

## Features:

- Finger rings are not supplied on ½" - 1" Dixon couplings.
- ½" Dixon coupler has only one cam arm.
- Couplers are supplied standard with a Buna-N gasket. Other gasket types are available on pages 74-76.



356T6 aluminum



aluminum hard coat



brass

Size	356T6 Aluminum		Aluminum Hard Coat		Brass	
	Part #	Price/E	Part #	Price/E	Part #	Price/E
½"	<b>50-C-AL</b>	<b>\$21.50</b>	---	---	<b>50-C-BR</b>	<b>\$46.40</b>
¾"	<b>75-C-AL</b>	<b>24.70</b>	---	---	<b>75-C-BR</b>	<b>50.95</b>
1"	<b>100-C-AL</b>	<b>26.25</b>	---	---	<b>100-C-BR</b>	<b>60.50</b>
1¼"	<b>125-C-AL</b>	<b>57.00</b>	---	---	<b>125-C-BR</b>	<b>88.00</b>
1½"	<b>150-C-AL</b>	<b>33.40</b>	<b>150-C-ALH</b>	<b>\$44.70</b>	<b>150-C-BR</b>	<b>83.60</b>
2"	<b>200-C-AL</b>	<b>37.25</b>	<b>200-C-ALH</b>	<b>55.90</b>	<b>200-C-BR</b>	<b>103.30</b>
2½"	<b>250-C-AL</b>	<b>67.60</b>	---	---	<b>250-C-BR</b>	<b>136.00</b>
3"	<b>300-C-AL</b>	<b>58.60</b>	<b>300-C-ALH</b>	<b>85.80</b>	<b>300-C-BR</b>	<b>189.00</b>
4"	<b>400-C-AL</b>	<b>79.60</b>	<b>400-C-ALH</b>	<b>111.40</b>	<b>400-C-BR</b>	<b>238.00</b>
5"	<b>500-C-AL</b>	<b>123.85</b>	---	---	---	---
6"	<b>600-C-AL</b>	<b>191.20</b>	<b>600-C-ALH</b>	<b>251.00</b>	<b>600-C-BR</b>	<b>795.00</b>
8"	<b>800-C-AL</b> <sup>1</sup>	<b>757.00</b>	---	---	---	---



<sup>1</sup> Dixon and Boss-Lock cam and groove couplings *do not interchange in the 8" and ½" sizes*. The 8" Dixon design has 4 cam arms, Boss-Lock design has 2 cam arms.



unplated malleable iron



316 stainless

Size	Unplated Malleable Iron		316 Stainless Steel	
	Part #	Price/E	Part #	Price/E
½"	---	---	<b>50-C-SS</b>	<b>\$57.60</b>
¾"	---	---	<b>75-C-SS</b>	<b>69.10</b>
1"	---	---	<b>100-C-SS</b>	<b>79.30</b>
1¼"	---	---	<b>125-C-SS</b>	<b>135.00</b>
1½"	<b>150-C-MI</b>	<b>\$50.25</b>	<b>150-C-SS</b>	<b>96.60</b>
2"	<b>200-C-MI</b>	<b>54.00</b>	<b>200-C-SS</b>	<b>114.25</b>
2½"	---	---	<b>250-C-SS</b>	<b>284.00</b>
3"	<b>300-C-MI</b> <sup>2</sup>	<b>87.00</b>	<b>300-C-SS</b>	<b>198.70</b>
4"	<b>400-C-MI</b> <sup>1,2</sup>	<b>112.20</b>	<b>400-C-SS</b>	<b>336.00</b>
5"	---	---	<b>500-C-SS</b>	<b>474.00</b>
6"	<b>600-C-MI</b> <sup>1,2</sup>	<b>210.00</b>	<b>600-C-SS</b>	<b>548.00</b>

<sup>1</sup> Suitable for use with King Crimp sleeves and ferrules, see pages 14-18.

<sup>2</sup> ductile iron