


The Timken Company

4500 Mt Pleasant St. NW

N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number 312NPP, Fafnir® Deep Groove Ball Bearings (9100K, 200K, 300K)

Radial ball bearings consist of an inner and outer ring with a cage containing a complement of precision balls. The standard Conrad-type bearing has a deep-groove construction capable of handling radial and axial loads from either direction in versatile designs that permit relatively high-speed operation.

In addition to standard single-row deep groove bearings, Timken offers special designs, including a maximum capacity series and an extra large (XLS) radial series bearing.

Size range: 3 mm


[more](#)

[Specifications](#) | [Dimensions](#) | [Basic Load Ratings](#) | [Factors](#) | [Abutment and Fillet Dimensions](#)

Specifications

Design Units	Metric
d - Bore	60 mm
Ball Type	STEEL
Manufacturing Part Number	312NPPFS50000

Dimensions



D - Outer Diameter	130 mm 5.118 in
Bearing Width	31 mm 1.2205 in

Basic Load Ratings

Ce - Dynamic Radial Rating¹	90700 N 20400 lbf
C0 - Static Radial Rating	51800 N 11700 lbf

Factors

Limiting Speed (Grease)	3158 rpm
Limiting Speed (Oil)	3684 rpm


Abutment and Fillet Dimensions

R - Inner Ring "To Clear" Radius²	2.11 mm 0.083 in
r - Outer Ring "To Clear" Radius³	2.11 mm 0.083 in
da - Inner Ring Backing Diameter	72.1 mm 2.8387 in
Da - Outer Ring Backing Diameter	118.11 mm 4.6500 in

¹ Based on 10^6 revolutions of calculated fatigue life.

² Maximum housing fillet radius that bearing corners will clear.

³ Maximum shaft fillet radius that bearing corners will clear.



METRIC UNITS

Number of Balls Per Row 8
 Bearing Weight 1.764 kg

TIMKEN®

THE TIMKEN COMPANY
 NORTH CANTON, OHIO USA

312NPP
 Fafnir® Deep Groove Ball Bearings (9100K, 200K, 300K)

Dynamic Radial Rating 90700 N
 Static Radial Rating 51800 N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY