


**The Timken Company**

4500 Mt Pleasant St. NW

N. Canton, OH 44720

**Phone:** (234) 262-3000

**E-Mail:** [CustomerCAD@timken.com](mailto:CustomerCAD@timken.com) • **Web site:** [www.timken.com](http://www.timken.com)

## Part Number 215KDD, Fafnir® Deep Groove Ball Bearings (9100K, 200K, 300K)

Radial ball bearings consist of an inner and outer ring with a cage containing a complement of precision balls. The standard Conrad-type bearing has a deep-groove construction capable of handling radial and axial loads from either direction in versatile designs that permit relatively high-speed operation.

In addition to standard single-row deep groove bearings, Timken offers special designs, including a maximum capacity series and an extra large (XLS) radial series bearing.

Size range: 3 mm


[more](#)

[Specifications](#) | [Dimensions](#) | [Basic Load Ratings](#) | [Factors](#) | [Abutment and Fillet Dimensions](#)

### Specifications

<b>Design Units</b>	Metric
<b>d - Bore</b>	75 mm
<b>Ball Type</b>	STEEL
<b>Manufacturing Part Number</b>	215KDDC1

### Dimensions



<b>D - Outer Diameter</b>	130 mm 5.118 in
<b>Bearing Width</b>	25 mm 0.9843 in

## Basic Load Ratings

<b>Ce - Dynamic Radial Rating<sup>1</sup></b>	68900 N 15500 lbf
<b>C0 - Static Radial Rating</b>	44800 N 10100 lbf

## Factors

<b>Limiting Speed (Grease)</b>	2927 rpm
<b>Limiting Speed (Oil)</b>	3415 rpm


## Abutment and Fillet Dimensions

<b>R - Inner Ring "To Clear" Radius<sup>2</sup></b>	1.5 mm 0.059 in
<b>r - Outer Ring "To Clear" Radius<sup>3</sup></b>	1.5 mm 0.059 in
<b>da - Inner Ring Backing Diameter</b>	82.60 mm 3.2520 in
<b>Da - Outer Ring Backing Diameter</b>	120.90 mm 4.760 in

<sup>1</sup> Based on  $10^6$  revolutions of calculated fatigue life.

<sup>2</sup> Maximum housing fillet radius that bearing corners will clear.

<sup>3</sup> Maximum shaft fillet radius that bearing corners will clear.



METRIC UNITS

Number of Balls Per Row	10
Bearing Weight	1.197 kg

**TIMKEN**®

---

**THE TIMKEN COMPANY**  
NORTH CANTON, OHIO USA

<b>215KDD</b>	
Fafnir® Deep Groove Ball Bearings (9100K, 200K, 300K)	
Dynamic Radial Rating	68900 N
Static Radial Rating	44800 N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

**FOR DISCUSSION ONLY**