



The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number 9105PP, Fafnir® Deep Groove Ball Bearings (9100K, 200K, 300K)

Radial ball bearings consist of an inner and outer ring with a cage containing a complement of precision balls. The standard Conrad-type bearing has a deep-groove construction capable of handling radial and axial loads from either direction in versatile designs that permit relatively high-speed operation.

In addition to standard single-row deep groove bearings, Timken offers special designs, including a maximum capacity series and an extra large (XLS) radial series bearing.

Size range: 3 mm



[more](#)

[Specifications](#) | [Dimensions](#) | [Basic Load Ratings](#) | [Factors](#) | [Abutment and Fillet Dimensions](#)

Specifications	
Design Units	Metric
d - Bore	25 mm
Ball Type	STEEL
Manufacturing Part Number	9105PP Z5 FS50000

Dimensions	



D - Outer Diameter	47 mm 1.85 in
Bearing Width	12 mm 0.4724 in

Basic Load Ratings

Ce - Dynamic Radial Rating¹	11200 N 2510 lbf
C0 - Static Radial Rating	5850 N 1320 lbf

Factors

Limiting Speed (Grease)	8333 rpm
Limiting Speed (Oil)	9722 rpm


Abutment and Fillet Dimensions

R - Inner Ring "To Clear" Radius²	0.6 mm 0.024 in
r - Outer Ring "To Clear" Radius³	0.6 mm 0.024 in
da - Inner Ring Backing Diameter	27.40 mm 1.0787 in
Da - Outer Ring Backing Diameter	41.91 mm 1.6500 in

¹ Based on 10^6 revolutions of calculated fatigue life.

² Maximum housing fillet radius that bearing corners will clear.

³ Maximum shaft fillet radius that bearing corners will clear.



METRIC UNITS

Number of Balls Per Row Bearing Weight	10 0.077 kg	TIMKEN® THE TIMKEN COMPANY NORTH CANTON, OHIO USA	9105PP Fafnir® Deep Groove Ball Bearings (9100K, 200K, 300K) Dynamic Radial Rating Static Radial Rating 11200 5850 N N	
	Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.			FOR DISCUSSION ONLY