


The Timken Company

4500 Mt Pleasant St. NW

N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number 6016-2RS-C3, Deep Groove Ball Bearings (6000, 6200, 6300, 6400)

Timken's deep groove ball bearings deliver reliable performance in a wide range of applications and conditions. With super-finished raceways and controlled geometries, our premium design helps ensure consistent quality.



[Specifications](#) | [Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

| | |
|---------------------|---------------|
| Clearance | C3 |
| Bore Size d | 80 mm |
| Features | Contact Seals |
| Bearing Type | Standard DGBB |

Dimensions

| | |
|-----------------------------|--------|
| Outside Diameter D | 125 mm |
| Outside Ring Width B | 22 mm |
| Radius Rs min | 1.1 mm |



Basic Load Ratings


| | |
|---------------------------------|---------|
| Cr - Dynamic Load Rating | 47500 N |
|---------------------------------|---------|

| | |
|---------------------------------|---------|
| C0r - Static Load Rating | 39800 N |
|---------------------------------|---------|

Factors

| | |
|-------------------------------|----------|
| Grease Reference Speed | 5800 rpm |
|-------------------------------|----------|

| | |
|----------------------------|----------|
| Oil Reference Speed | 8400 rpm |
|----------------------------|----------|



METRIC UNITS

Weight 0.82 kg

TIMKEN®

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

6016-2RS-C3
Deep Groove Ball Bearings (6000, 6200, 6300, 6400)

Dynamic Load Rating 47500 N
Static Load Rating 39800 N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY