


**The Timken Company**

4500 Mt Pleasant St. NW

N. Canton, OH 44720

**Phone:** (234) 262-3000

**E-Mail:** [CustomerCAD@timken.com](mailto:CustomerCAD@timken.com) • **Web site:** [www.timken.com](http://www.timken.com)

## Part Number 608-ZZ, Miniature Ball Bearings (600, 610, 620, 630)

Timken's deep groove ball bearings deliver reliable performance in a wide range of applications and conditions. With super-finished raceways and controlled geometries, our premium design helps ensure consistent quality.



[Specifications](#) | [Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

### Specifications

<b>Bore Size d</b>	8 mm
<b>Features</b>	Shields
<b>Bearing Type</b>	Standard DGBB

### Dimensions

<b>Outside Diameter D</b>	22 mm
<b>Outside Ring Width B</b>	7 mm
<b>Radius Rs min</b>	0.3 mm



## Basic Load Ratings


**Cr - Dynamic Load Rating** 3300 N

**C0r - Static Load Rating** 1400 N

## Factors

**Grease Limiting Speed** 33000 rpm

**Oil Limiting Speed** 39000 rpm



METRIC UNITS

Weight 0.011 kg

**TIMKEN**®

**THE TIMKEN COMPANY**  
NORTH CANTON, OHIO USA

**608-ZZ**  
Miniature Ball Bearings (600, 610, 620, 630)

Dynamic Load Rating 3300 N  
Static Load Rating 1400 N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

**FOR DISCUSSION ONLY**