


The Timken Company

4500 Mt Pleasant St. NW

N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com
Part Number 6014-Z-NR-C3, Deep Groove Ball Bearings (6000, 6200, 6300, 6400)

Timken's deep groove ball bearings deliver reliable performance in a wide range of applications and conditions. With super-finished raceways and controlled geometries, our premium design helps ensure consistent quality.



[Specifications](#) | [Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

Clearance	C3
Bore Size d	70 mm
Features	One Shield With Snap Ring
Bearing Type	Standard DGBB

Dimensions

Outside Diameter D	110 mm
Outside Ring Width B	20 mm
Radius Rs min	1.1 mm



Snap Ring Diameter D2 max	116.600 mm
----------------------------------	------------

Snap Ring Width f max	2.460 mm
------------------------------	----------

Basic Load Ratings


Cr - Dynamic Load Rating	38600 N
---------------------------------	---------

C0r - Static Load Rating	30400 N
---------------------------------	---------

Factors

Grease Reference Speed	6400 rpm
-------------------------------	----------

Oil Reference Speed	9300 rpm
----------------------------	----------



METRIC UNITS

Weight 0.57 kg

TIMKEN®

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

6014-Z-NR-C3
Deep Groove Ball Bearings (6000, 6200, 6300, 6400)

Dynamic Load Rating 38600 N
Static Load Rating 30400 N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY