


The Timken Company

4500 Mt Pleasant St. NW

N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number 2MMV9104HXVVSUMFS934, Fafnir® High Speed Spindle Angular Contact Ball Bearings (9300HX, 9100HX)

Timken® angular contact ball bearings are designed for combination radial and axial loading. Single-row bearings have high thrust capacity in one direction. Some single-row bearings are specifically designed for duplex mounting in sets for maximum performance.



[Specifications](#) | [Dimensions](#) | [Basic Load Ratings](#) | [Factors](#) | [Abutment and Fillet Dimensions](#)

Specifications

Rows per Set	Single
Seal Type	High Speed
Design Units	Metric
d - Bore	20 mm
Ball Type	STEEL
Cage Type	CR - Phenolic Outer Land Riding Cage
Precision Rating	ISO P4S (ABEC 7/9)



Dimensions

D - Outer Diameter	42 mm 1.6535 in
Bearing Width	12 mm 0.4724 in
Total Width	12 mm 0.4724 in
Contact Angle	15 °

Basic Load Ratings

C0 - Static Radial Rating (per row)	3740 N 840 lbf
Ce - Dynamic Radial Rating (per row)¹	8730 N 1960 lbf
C1 ISO - Dynamic Radial Rating (per row)	7940 N 1780 lbf

Factors


Limiting Speed (Grease) (per row)	48900 rpm
Limiting Speed (Oil)	97800 rpm

Abutment and Fillet Dimensions

R - Inner Ring "To Clear" Radius²	0.6 mm 0.024 in
r - Outer Ring "To Clear" Radius³	0.6 mm 0.024 in
da - Inner Ring Backing Diameter	24.8 mm 0.980 in

Da - Outer Ring Backing Diameter	37.7 mm 1.490 in
---	---------------------

- ¹ Based on 10^6 revolutions of calculated fatigue life.
- ² Maximum housing fillet radius that bearing corners will clear.
- ³ Maximum shaft fillet radius that bearing corners will clear.



METRIC UNITS

Number of Balls Per Row	12
Bearing Weight	0.064 kg

TIMKEN®

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

2MMV9104HXVVSUMFS934
Fafnir® High Speed Spindle Angular Contact Ball Bearings (9300HX, 9100HX)

Dynamic Radial Rating	8730	N
Static Radial Rating	3740	N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY