


The Timken Company

4500 Mt Pleasant St. NW

N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com
Part Number 22215EJW33C4, Spherical Roller Bearings - Steel Cage

Spherical bearings are designed to manage high radial loads even when misalignment, poor lubrication, contamination, extreme speeds or critical application stresses are present.



[Specifications](#) | [Factors](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#)

Specifications

UPC Code	087796169098
Design Unit	Metric
d - Bore	75 mm
Lubrication Type	Standard Grease
Cage Type	EJ
Cage Material	Steel
Superseded Part	22215CJW33C4

Factors


e - ISO Factor¹ 0.22

Y0 - ISO Factor²	3.07
Y1 - ISO Factor³	3.14
Y2 - ISO Factor⁴	4.67
Reference Thermal Speed Rating (Grease)	3700 rpm
Reference Thermal Speed Rating (Oil)⁵	4600 rpm
Cg - Geometry Factor⁶	0.0547

Dimensions

D - Outer Diameter	130 mm 5.1181 in
B' - Inner Ring Width	31 mm 1.2205 in
B - Outer Ring Width	31 mm 1.2205 in

Abutment and Fillet Dimensions

R - Inner Ring "To Clear" Radius⁷	1.5 mm 0.060 in
r - Outer Ring "To Clear" Radius⁸	1.5 mm 0.06 in
da - Inner Ring Backing Diameter	88.000 mm 3.5000 in
Da - Outer Ring Backing Diameter	120.000 mm 4.700 in

Basic Load Ratings

C0 - Static Radial Rating	240000 N 54100 lbf
C1(2) - Dynamic Radial Rating (Two-Rows)	222000 N 49900 lbf

¹ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

² These factors apply for both inch and metric calculations. See engineering

³ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.


⁴ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁵ See thermal speed ratings in the engineering section.

⁶ Geometry constant for Lubrication Life Adjustment Factor a_3 .

⁷ Maximum housing fillet radius that bearing corners will clear.

⁸ These maximum fillet radii will be cleared by the bearing corners.



METRIC UNITS

Number of Rollers Per Row	19
ISO Factor e	0.22
ISO Factor Y0	3.07
ISO Factor Y1	3.14
ISO Factor Y2	4.67
Bearing Weight	kg
Cage Type	EJ
Cage Material	Steel

TIMKEN®

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

22215EJW33C4
SRB ASSEMBLY

Dynamic Radial Rating (Two Rows)	222000	N
Static Radial Rating	240000	N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY