


The Timken Company

4500 Mt Pleasant St. NW

N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com
Part Number 22217KEMW33, Spherical Roller Bearings - Brass Cage

Spherical bearings are designed to manage high radial loads even when misalignment, poor lubrication, contamination, extreme speeds or critical application stresses are present.



[Specifications](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

Design Unit	Metric
d - Bore	85 mm
Bore_Taper	1/12
Cage Type	EM
Cage Material	Brass
Superseded Part	22217KYMW33

Dimensions

D - Outer Diameter	150 mm
B' - Inner Ring Width	36 mm



B - Outer Ring Width	36 mm
-----------------------------	-------

Abutment and Fillet Dimensions

R - Inner Ring "To Clear" Radius¹	2 mm
r - Outer Ring "To Clear" Radius²	2 mm
da - Inner Ring Backing Diameter	101.000 mm
Da - Outer Ring Backing Diameter	139.000 mm

Basic Load Ratings

C0 - Static Radial Rating	302000 N
C1(2) - Dynamic Radial Rating (Two-Rows)	286000 N

Factors

e - ISO Factor³	0.22
Y0 - ISO Factor⁴	3
Y1 - ISO Factor⁵	3.07
Y2 - ISO Factor⁶	4.57
Reference Thermal Speed Rating (Grease)	3500 rpm
Reference Thermal Speed Rating (Oil)⁷	4200 rpm
Cg - Geometry Factor⁸	0.0595

¹ Maximum housing fillet radius that bearing corners will clear.

² Maximum shaft fillet radius that bearing corners will clear.

³ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.


⁴ These factors apply for both inch and metric calculations. See engineering

⁵ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁶ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁷ See thermal speed ratings in the engineering section.

⁸ Geometry constant for Lubrication Life Adjustment Factor a_3 .



METRIC UNITS

Number of Rollers Per Row	17
ISO Factor e	0.22
ISO Factor Y0	3.00
ISO Factor Y1	3.07
ISO Factor Y2	4.57
Bearing Weight	2.7 kg
Cage Type	EM
Cage Material	Brass
Bore Taper	1/12

TIMKEN®

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

22217KEMW33
SRB ASSEMBLY

Dynamic Radial Rating (Two Rows)	286000	N
Static Radial Rating	302000	N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY