



The Timken Company

4500 Mt Pleasant St. NW


N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number 22226KEJW33C3, Spherical Roller Bearings - Steel Cage

Spherical bearings are designed to manage high radial loads even when misalignment, poor lubrication, contamination, extreme speeds or critical application stresses are present.



[Specifications](#) | [Factors](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#)

Specifications

UPC Code	087796025493
Design Unit	Metric
d - Bore	130 mm
Lubrication Type	Standard Grease
Bore_Taper	1/12
Cage Type	EJ
Cage Material	Steel
Superseded Part	22226KCJW33C3



e - ISO Factor¹	0.26
Y0 - ISO Factor²	2.56
Y1 - ISO Factor³	2.62
Y2 - ISO Factor⁴	3.9
Reference Thermal Speed Rating (Grease)	2400 rpm
Reference Thermal Speed Rating (Oil)⁵	2900 rpm
Cg - Geometry Factor⁶	0.0819

Dimensions

D - Outer Diameter	230 mm 9.0551 in
B' - Inner Ring Width	64 mm 2.5197 in
B - Outer Ring Width	64 mm 2.5197 in

Abutment and Fillet Dimensions

R - Inner Ring "To Clear" Radius⁷	2.5 mm 0.100 in
r - Outer Ring "To Clear" Radius⁸	2.5 mm 0.1 in
da - Inner Ring Backing Diameter	155 mm 6.1000 in
Da - Outer Ring Backing Diameter	210.000 mm 8.300 in

C0 - Static Radial Rating	945000 N 212000 lbf
C1(2) - Dynamic Radial Rating (Two-Rows)	757000 N 170000 lbf

¹ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

² These factors apply for both inch and metric calculations. See engineering

³ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.


⁴ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁵ See thermal speed ratings in the engineering section.

⁶ Geometry constant for Lubrication Life Adjustment Factor a31.

⁷ Maximum housing fillet radius that bearing corners will clear.

⁸ These maximum fillet radii will be cleared by the bearing corners.



METRIC UNITS

Number of Rollers Per Row	20
ISO Factor e	0.26
ISO Factor Y0	2.56
ISO Factor Y1	2.62
ISO Factor Y2	3.90
Bearing Weight	kg
Cage Type	EJ
Cage Material	Steel
Bore Taper	1/12

TIMKEN®

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

22226KEJW33C3
SRB ASSEMBLY

Dynamic Radial Rating (Two Rows)	757000	N
Static Radial Rating	945000	N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY