



The Timken Company

4500 Mt Pleasant St. NW


N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number 22322KEJW33C3, Spherical Roller Bearings - Steel Cage

Spherical bearings are designed to manage high radial loads even when misalignment, poor lubrication, contamination, extreme speeds or critical application stresses are present.



[Specifications](#) | [Factors](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#)

Specifications

UPC Code	087796027237
Design Unit	Metric
d - Bore	110 mm
Lubrication Type	Standard Grease
Bore_Taper	1/12
Cage Type	EJ
Cage Material	Steel
Superseded Part	22322KCJW33C3



e - ISO Factor¹	0.32
Y0 - ISO Factor²	2.04
Y1 - ISO Factor³	2.08
Y2 - ISO Factor⁴	3.1
Reference Thermal Speed Rating (Grease)	2100 rpm
Reference Thermal Speed Rating (Oil)⁵	2500 rpm
Cg - Geometry Factor⁶	0.0792

Dimensions

D - Outer Diameter	240 mm 9.4488 in
B' - Inner Ring Width	80 mm 3.1496 in
B - Outer Ring Width	80 mm 3.1496 in

Abutment and Fillet Dimensions

R - Inner Ring "To Clear" Radius⁷	2.5 mm 0.100 in
r - Outer Ring "To Clear" Radius⁸	2.5 mm 0.1 in
da - Inner Ring Backing Diameter	144.0 mm 5.7000 in
Da - Outer Ring Backing Diameter	215.000 mm 8.5000 in

Basic Load Ratings

C0 - Static Radial Rating	1050000 N 236000 lbf
----------------------------------	-------------------------

C1(2) - Dynamic Radial Rating (Two-Rows)	949000 N 213000 lbf
---	------------------------

¹ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

² These factors apply for both inch and metric calculations. See engineering

³ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.


⁴ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁵ See thermal speed ratings in the engineering section.

⁶ Geometry constant for Lubrication Life Adjustment Factor a_3 .


⁷ Maximum housing fillet radius that bearing corners will clear.

⁸ These maximum fillet radii will be cleared by the bearing corners.



METRIC UNITS

Number of Rollers Per Row	15
ISO Factor e	0.32
ISO Factor Y0	2.04
ISO Factor Y1	2.08
ISO Factor Y2	3.10
Bearing Weight	kg
Cage Type	EJ
Cage Material	Steel
Bore Taper	1/12



THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

22322KEJW33C3
SRB ASSEMBLY

Dynamic Radial Rating (Two Rows)	949000	N
Static Radial Rating	1050000	N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY